



## Eye-bolt (DIN-580)

### Product information

High-alloyed steel eyebolt. Eye bolts may only be tightened by hand.  
 Safe workload, under a maximum angle of 60° as shown.  
 The lifting eye must not be loaded sideways.

**Marking:** According to standard, CE-marked  
**Standard:** EN 1677-1, DIN 580

**Safety factor:** 4  
**Grade:** 8

Part code	Code	WLL ton	Thread mm	Model	A mm	B mm	C mm	D, mm	Mmm mm	Weight kg	Delivery time
2675308	8717365115202	0,4	M8	DIN580-G8-M8	34	7	20	13	M8 x 1,25	0,05	3
2675310	8717365115219	0,7	M10	DIN580-G8-M10	38	8	22	17	M10 x 1,50	0,07	3
2675312	8717365115226	1	M12	DIN580-G8-M12	47	10	26	21	M12 x 1.75	0,13	3
2675316	8717365115233	1,5	M16	DIN580-G8-M16	64	14	35	27	M16 x 2.00	0,34	3
2675320	8717365115240	2,5	M20	DIN580-G8-M20	73	16	39	30	M20 x 2.50	0,52	3
2675324	8717365115257	4	M24	DIN580-G8-M24	95	20	54	36	M24 x 3.00	0,99	3