



Bow shackle with screwpin G-4161

Product information



Galvanized steel with a high tensile strength suitable for temperatures between -20 ° C and + 200 ° C. Equipped with screwpin.

Marking: According to standard, CE-marked

Standard: EN 13889

Safety factor: 6

Grade: 6

Part code	GTIN No.	WLL ton	Model	A mm	B mm	C mm	D mm	E mm	Weight kg	Delivery time
3011001	8717365013331	0,5	G4161-1/4	7	8	12	29	20	0,06	3
3011003	8717365013348	0,75	G4161-5/16	9	10	13,5	32	21	0,11	3
3011005	8717365013355	1	G4161-3/8	10	11	16,1	36	26	0,15	3
3011007	8717365013362	1,5	G4161-7/16	11	13	18	43	29	0,21	3
3011009	8717365013379	2	G4161-1/2	13,5	16	22	51	32	0,37	3
3011011	8717365013386	3,25	G4161-5/8	16	19	27	64	43	0,65	3
3011013	8717365013393	4,75	G4161-3/4	19	22	31	76	51	1,06	3
3011015	8717365013409	6,5	G4161-7/8	22	25	36	83	58	1,56	3
3011017	8717365013416	8,5	G4161-1	25	28	43	95	68	2,32	3
3011018	8717365013423	9,5	G4161-1.1/8	28	32	47	108	75	3,28	3
3011019	8717365013430	12	G4161-1.1/4	32	35	51	115	83	4,51	3
3011020	8717365013447	13,5	G4161-1.3/8	35	38	57	133	92	5,93	3
3011021	8717365013454	17	G4161-1.1/2	38	42	60	146	99	7,89	3
3011023	8717365013461	25	G4161-1.3/4	45	50	74	178	126	13,4	3
3011025	8717365022968	35	G4161-2	50	57	83	197	138	18,15	7
3011027	8717365258541	42,5	G4161-2.1/4	57	65	95	222	160	26,29	7
3011029	8717365023583	55	G4161-2.1/2	65	70	105	260	180	37,6	3

Blueprint

