




DL winches (NOT FOR LIFTING)

Product information



DL zinc winch only for pulling.

Properties

- Demountable crank (DL-2500 en DL-3500).
- Zinc-plated housing with zinc-plated drum (Model DL-35 is fitted with a black drum).
- Hardened steel gears.
- The DL-900A, DL-1000A and DL-1402A versions have a pawl that works in one direction with freewheel mode.
- The DL-2500AB and DL-3500B versions have a double speed and are also equipped with a manually operated brake.

Standard delivery

- Without cable.

Option

- Steel wire rope with safety hook.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

Part Code	GTIN No.	WLL ton	Model	Cable Diameter mm	Lift/crank turn (mm)	Gear ratio	Max. reel capacity mm	Force on the handle (kg)	Drum mm	Length handle mm	Weight kg
2117001	8717365008924	0,408	DL-900A	5	19	3.2:1	10,9	7	16 x 50	178	2
2117003	8717365008931	0,499	DL-1100A	5	18	3.7:1	22,2	9	22 x 53	178	3
2117005	8717365008948	0,635	DL-1402A	6	16	4.4:1	14,2	8	22 x 50	241	4
2117007	8717365008955	1,134	DL-2500AB	8	16	17.3:1 - 5.4:1	23	5	28 x 60	241	7
2117009	8717365008962	1,589	DL-3500B	10	16	12:1 - 6:1	12,3	13	33 x 70	241	10

Blueprint

