



Low Headroom Air Chain Hoist Red Rooster TMH

Product information

The TMH-LHR series is a low headroom air hoist from Red Rooster. It has the highest lifting speed with the lowest headroom on the hoist market. With the high M4 classification of mechanism (ISO 4301-1) this high speed air hoist is extremely durable and will guarantee the continuity of your process. The TMH hoists are designed to operate at full lifting capacity with an air pressure from 4 – 6.3 bar. For full speed operation the hoist air pressure should be 6.3 bar.

Standard features

- Toku rotary vane motor
- ATEX zone 2 specification
- Robust 3 step planetary gearbox
- Failsafe automatic internal disc brake
- Upper & lower limit switches
- *Internal silencing down to 80 dB(A)*
- Alloy safety swivel hooks with safety catch
- Load chain of European manufacture EN818-7
- Automatic load limiter

Optional:

- Marine Specification/Corrosion resistant
- Paint systems from C2 - Industrial to C5 - Offshore specification (Red finish as standard. Other RAL colours available on request).
- Choice of pendants.
- Radio control pendant for electro pneumatic controls.
- Control systems.
- Chain collectors (PVC, galvanised or stainless steel).
- Various types of hook or clevis available.
- Air supply systems and valves.
- Air Service unit.
- Piped away exhaust air.
- In house design for "specials".
- Festoon systems.
- Main air shut off valve.

ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Material: Housing: cast steel

Part code	WLL	Number of falls	Type	Lifting speed without load		Lifting speed with load		Lowering speed with load		Air consumption Hoist	Air consumption Trolley	Weight	Delivery time		
				ton	m/min	m/min	m/min	kg/min	kg/min						
0702999	3	1	TMH-3000-LHR		10.8		5.4		10.2		56		25	275	7
0702999	6	2	TMH-6000/2-LHR		5.4		2.7		5.1		56		25	300	7
0702999	9	3	TMH-9000/3-LHR		3.6		1.8		3.4		56		40	375	7
0702999	10	2	TMH-10/2-LHR		3.5		1.6		3.2		58		50	545	7
0702999	12	4	TMH-12000/4-LHR		2.7		1.35		2.55		56		40	400	7
0702999	15	5	TMH-15000/5-LHR		2.16		1.08		2.04		56		40	550	7
0702999	15	3	TMH-15/3-LHR		2.2		1.05		2.1		58		100	690	7
0702999	20	4	TMH-20/4-LHR		1.6		0.8		1.6		58		100	890	7