



Portable swivel davit 125-250-500

Product information

Portable ergonomic modern design swivel davit for lifting.
Easily foldable, ready to use in a few seconds.
Integrated winch.
Including 8 meter wire rope (d5 mm) with hook

Specifications:

- Easy to transport, only 25 kg
- 360 degrees rotation over a built in ball bearing
- Maintenance free
- Adjustable crank
- The numbers in the product name correspond with the hoisting capacities on the first cable layer
- Beam reach differs from 60cm, 80cm to 100cm

Optional:

- zinc-plated finish (6 - 8 micron) (EV)
- stainless steel grade SAE 316 (SST316)
- ATEX certified (EX)

Accessories:

- floor, wall and in-cement floor sockets
- carry bag and rain protection cover

Marking: According to standard, CE-marked

Standard: EN 13157

Safety factor: 4:1

Part code	Code	WLL ton	Model	Rope Ø mm	Lift/crank turn (mm)	Rope capacity m	Hand force max. kg	WLL Lifting outer layer (kg)	Weight kg	Delivery time
3750125	8717365187780	0.125	SD125	4	20	18	10	125	30	7
3750250	8717365187797	0.25	SD250	4	20	18	10	250	30	7
3750500	8717365187803	0.5	SD500	5	20	13	10	268	30	7

Blueprint

