REMA 75 YEARS HOISTING & LIFTING Work made easy.

Chain Hoist Rema® Select 200

Product information



The Rema® Select 200 OD is equipped with an overload protection from 500 kg. It is a robust manual chain hoist for heavy and intensive use where safety, ergonomics and a low operating effort are paramount.

Properties

- The new innovative overload protection ensures an improved safer operation of the hoist.
- Overload device system makes it possible to lower the load in a controlled way.
- Equipped with a double pawl system.
- Brake is provided with astbestos free friction discs.
- Top and bottom hooks are equipped with a robust latches.
- Load hooks gradually bend and do not break off suddenly.
- Galvanized load chain Grade 8.
- Galvanized hand chain.

Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operating height.
- Overload protection from 500 kg up to 10.000 kg.

Option

- Available in any other hoisting and operational heights.
- Chain bucker available up to 10 meter lifting height from 500 kg till 2000 kg.
- Short height in combination with REMA 211/212 trolley bij intermediate link, which replace the top hook.

Warning

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 13157, EN 818-7


REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA® 75 YEARS HOISTING & LIFTING Work made easy.

Chain Hoist Rema® Select 200

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
0120000-3	8717365263637	0.25	3	1	S200-250KG*-3M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	6
0120000-4	8717365263644	0.25	4	1	S200/250KG/4M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	7.4
0120000-5	8717365263651	0.25	5	1	S200/250KG/5M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	8.8
0120000-6	8717365263668	0.25	6	1	S200-250KG*-6M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	10.2
0120000-7	8717365092572	0.25	7	1	S200/250KG/7M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	11.6
0120000-8	8717365092589	0.25	8	1	S200/250KG/8M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	13
0120000-9	8717365092596	0.25	9	1	S200/250KG/9M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	14.4
0120000-10	8717365092602	0.25	10	1	S200/250KG/10M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	15.8
0120001-3	8717365263675	0.5	3	1	S200OD-500KG-3M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	10
0120001-4	8717365263682	0.5	4	1	S200OD/500KG/4M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	11.6
0120001-5	8717365263699	0.5	5	1	S200OD/500KG/5M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	13.2
0120001-6	8717365263705	0.5	6	1	S200OD-500KG-6M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	14.8
0120001-7	8717365092619	0.5	7	1	S200OD/500KG/7M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	16.4
0120001-8	8717365092626	0.5	8	1	S200OD/500KG/8M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	18

© November 2026 - All Rights Reserved

REMA® 75 YEARS HOISTING & LIFTING Work made easy.

Chain Hoist Rema® Select 200

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
0120001-9	8717365092633	0.5	9	1	S200OD/500KG/9M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	19.6
0120001-10	8717365092640	0.5	10	1	S200OD/500KG/10M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	21.2
0120003-3	8717365263712	1	3	1	S200OD-1000KG-3M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	12
0120003-4	8717365263729	1	4	1	S200OD/1000KG/4M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	13.9
0120003-5	8717365263736	1	5	1	S200OD/1000KG/5M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	15.8
0120003-6	8717365263743	1	6	1	S200OD-1000KG-6M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	17.7
0120003-7	8717365092657	1	7	1	S200OD/1000KG/7M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	19.6
0120003-8	8717365092664	1	8	1	S200OD/1000KG/8M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	21.5
0120003-9	8717365092671	1	9	1	S200OD/1000KG/9M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	23.4
0120003-10	8717365092688	1	10	1	S200OD/1000KG/10M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	25.3
0120005-3	8717365263750	1.5	3	1	S200OD-1500KG-3M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	16
0120005-4	8717365263767	1.5	4	1	S200OD/1500KG/4M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	18.2
0120005-5	8717365263774	1.5	5	1	S200OD/1500KG/5M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	20.4
0120005-6	8717365263781	1.5	6	1	S200OD-1500KG-6M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	22.6
0120005-7	8717365092695	1.5	7	1	S200OD/1500KG/7M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	24.8
0120005-8	8717365092701	1.5	8	1	S200OD/1500KG/8M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	27
0120005-9	8717365092718	1.5	9	1	S200OD/1500KG/9M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	29.2
0120005-10	8717365092725	1.5	10	1	S200OD/1500KG/10M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	31.4
0120007-3	8717365263798	2	3	1	S200OD-2000KG-3M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	20
0120007-4	8717365263804	2	4	1	S200OD/2000KG/4M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	22.4

© November 2026 - All Rights Reserved

REMA® 75 YEARS HOISTING & LIFTING Work made easy.

Chain Hoist Rema® Select 200

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
0120007-5	8717365263811	2	5	1	S200OD/2000KG/5M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	24.8
0120007-6	8717365263828	2	6	1	S200OD-2000KG-6M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	27.2
0120007-7	8717365092732	2	7	1	S200OD/2000KG/7M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	29.6
0120007-8	8717365092749	2	8	1	S200OD/2000KG/8M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	32
0120007-9	8717365092756	2	9	1	S200OD/2000KG/9M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	34.4
0120007-10	8717365092763	2	10	1	S200OD/2000KG/10M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	36.8
0120009	8717365261657	3	-	2	S200OD-3000KG	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	24
0120009-3	8717365263835	3	3	2	S200OD-3000KG-3M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	26
0120009-4	8717365263842	3	4	2	S200OD/3000KG/4M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	29.4
0120009-5	8717365263859	3	5	2	S200OD/3000KG/5M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	32.8
0120009-6	8717365263866	3	6	2	S200OD-3000KG-6M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	36.2
0120009-7	8717365092770	3	7	2	S200OD/3000KG/7M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	39.6
0120009-8	8717365092787	3	8	2	S200OD/3000KG/8M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	43
0120009-9	8717365092794	3	9	2	S200OD/3000KG/9M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	46.4
0120009-10	8717365092800	3	10	2	S200OD/3000KG/10M	7.1 x 19	5.0 x 23.7	510	34.3	220	158	37	50	510	49.8
0120011-3	8717365263873	5	3	2	S200OD-5000KG-3M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	41.5
0120011-4	8717365263880	5	4	2	S200OD/5000KG/4M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	46
0120011-5	8717365263897	5	5	2	S200OD/5000KG/5M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	50.5
0120011-6	8717365263903	5	6	2	S200OD-5000KG-6M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	55
0120011-7	8717365092817	5	7	2	S200OD/5000KG/7M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	59.5

REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA® 75 YEARS HOISTING & LIFTING Work made easy.

Chain Hoist Rema® Select 200

Technical data

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	H mm	Weight kg
0120011-8	8717365092824	5	8	2	S200OD/5000KG/8M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	64
0120011-9	8717365092831	5	9	2	S200OD/5000KG/9M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	68.5
0120011-10	8717365092848	5	10	2	S200OD/5000KG/10M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	73
0120013-3	8717365174582	7.5	3	3	S200OD-7500KG-3M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	50
0120013-4	8717365174599	7.5	4	3	S200OD/7500KG/4M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	57
0120013-5	8717365174605	7.5	5	3	S200OD/7500KG/5M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	64
0120013-6	8717365174612	7.5	6	3	S200OD-7500KG-6M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	71
0120013-7	8717365174629	7.5	7	3	S200OD/7500KG/7M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	77
0120013-8	8717365174636	7.5	8	3	S200OD/7500KG/8M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	84
0120013-9	8717365174643	7.5	9	3	S200OD/7500KG/9M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	91
0120013-10	8717365174650	7.5	10	3	S200OD/7500KG/10M	9.0 x 27	5.0 x 23.7	690	36.8	430	189	47	67	690	98
0120015-3	8717365174667	10	3	4	S200OD-10000KG-3M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	75
0120015-4	8717365174674	10	4	4	S200OD/10.000KG/4M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	83
0120015-5	8717365174681	10	5	4	S200OD/10.000KG/5M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	91
0120015-6	8717365174698	10	6	4	S200OD-10000KG-6M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	99
0120015-7	8717365174704	10	7	4	S200OD/10.000KG/7M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	107
0120015-8	8717365174711	10	8	4	S200OD/10.000KG/8M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	115
0120015-9	8717365174728	10	9	4	S200OD/10.000KG/9M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	123
0120015-10	8717365174735	10	10	4	S200OD/10.000KG/10M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	131

REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved