



KBT200OD low headroom hoist-trolley

Product information



Hand-operated trolley in combination with the Rema® Select 200OD hand chain hoist.
Only available in combination with the Rema® Select 200 OD manual chain hoist.

Properties

- Extremely low building height (135-235 mm).
- Suitable for beams with both straight and sloping flange.
- Maintenance-free ball bearings.
- Wheel rupture supports for extra safety.
- Hand chain operated trolley.
- Technical specifications for manual hoist see Rema® Select 200 OD chain hoist.

Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operation.

Option

- Available in other lifting and operating heights.

Marking: CE-marked

Part code	WLL ton	Number of falls	Model	Flange width mm	Load chain mm	Hand chain mm	Minimum radius mm	A, mm	B1 mm	B2 mm	C1 mm	C2 mm	D1 mm	D2 mm	E1 mm	E2 mm	F, mm	H, mm	L mm	M1 mm	M2 mm	Weight kg	Delivery time
0923001	1	2	KBT200OD-1	74-150	5.0 X 15	5.0 X 23.7	2,500	554	206	234	129	151	117	223	217	134	27.5	135	348	40	18	69	3
0923003	2	2	KBT200OD-2	82-156	6.3 X 19.1	5.0 X 23.7	4,000	684	254	406	149	211	165	265	240	152	36.5	160	392	50	24	118	2
0923005	3.2	2	KBT200OD-3.2	103-223	8.0 X 24.2	5.0 X 23.7	4,500	765	279	461	169	236	165	325	240	173	44	190	499	55	28	181	2
0923007	5	4	KBT200OD-5	119-215	8.0 X 24.2	5.0 X 23.7	6,000	873	336	524	201	279	184	327	259	180	39	235	512	65	37	293	2
0923009	6.3	4	KBT200OD-6.3	119-215	8.0 X 24.2	5.0 X 23.7	6,000	873	336	524	201	279	184	327	259	180	39	235	512	65	37	296	2

Blueprint

