



Chain Hoist Rema[®] X-Line

Product information



The Rema[®] X-Line hand hoist is the solution for all demanding lifting tasks. With low operating force and increased safety system, you work efficiently and safely. The asbestos-free friction discs and wear-resistant load chain make use even more comfortable. The gradual bulging under overload and the orange powder coating provide additional safety and visibility. Available from 3 meters lifting height and 2.5 meters operating height, the Rema[®] X-Line hand hoist is suitable for any demanding task.

Properties

- Low operating force at full load.
- Increased operational safety due to double pawl system.
- Brake is provided with asbestos free friction discs.
- Load chain wheel is made of wear-resistant alloy steel.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 8).
- Galvanized hand chain.
- Steel housing with orange colored powder coating.

Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operating height.

Option

- Available in any other hoisting and operational heights.

Norm:

- EN12100-1/2, EN13157, EN818-7

Marking: According to standard, CE-marked

Standard: EN 13157, EN 818-7

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D, mm	H, mm	Weight kg	Delivery time
0170000-3	8717365112539	0.25	3	1	X-CH/250KG/3M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	6	3
0170000-4	8717365112423	0.25	4	1	X-CH/250KG/4M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	7.4	3
0170000-5	8717365112430	0.25	5	1	X-CH/250KG/5M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	8.8	3
0170000-6	8717365112553	0.25	6	1	X-CH/250KG/6M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	10.2	3
0170000-7	8717365112447	0.25	7	1	X-CH/250KG/7M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	11.6	3
0170000-8	8717365112454	0.25	8	1	X-CH/250KG/8M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	13	3
0170000-9	8717365112461	0.25	9	1	X-CH/250KG/9M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	14.4	3
0170000-10	8717365112478	0.25	10	1	X-CH/250KG/10M	4.0 x 12	5.0 x 23.7	260	23.5	108	106	20	30	260	15.8	3
0170001-3	8717365096211	0.5	3	1	X-CH/500KG/3M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	10	3
0170001-4	8717365096440	0.5	4	1	X-CH/500KG/4M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	11.6	3
0170001-5	8717365096457	0.5	5	1	X-CH/500KG/5M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	13.2	3
0170001-6	8717365096228	0.5	6	1	X-CH/500KG/6M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	14.8	3
0170001-7	8717365096464	0.5	7	1	X-CH/500KG/7M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	16.4	3
0170001-8	8717365096471	0.5	8	1	X-CH/500KG/8M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	18	3
0170001-9	8717365096488	0.5	9	1	X-CH/500KG/9M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	19.6	3
0170001-10	8717365096495	0.5	10	1	X-CH/500KG/10M	5.0 x 15	5.0 x 23.7	280	24.9	130	128	22	34	280	21.2	3
0170003-3	8717365096235	1	3	1	X-CH/1000KG/3M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	12	3
0170003-4	8717365096501	1	4	1	X-CH/1000KG/4M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	13.9	3
0170003-5	8717365096518	1	5	1	X-CH/1000KG/5M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	15.8	3
0170003-6	8717365096242	1	6	1	X-CH/1000KG/6M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	17.7	3
0170003-7	8717365096525	1	7	1	X-CH/1000KG/7M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	19.6	3

0170003-8	8717365096532	1	8	1	X-CH/1000KG/8M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	21.5	3
0170003-9	8717365096549	1	9	1	X-CH/1000KG/9M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	23.4	3
0170003-10	8717365096556	1	10	1	X-CH/1000KG/10M	6.3 x 19	5.0 x 23.7	330	28.4	150	142	26	39	330	25.3	3
0170005-3	8717365096259	1.5	3	1	X-CH/1500KG/3M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	16	3
0170005-4	8717365096563	1.5	4	1	X-CH/1500KG/4M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	18.2	3
0170005-5	8717365096570	1.5	5	1	X-CH/1500KG/5M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	20.4	3
0170005-6	8717365096266	1.5	6	1	X-CH/1500KG/6M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	22.6	3
0170005-7	8717365096587	1.5	7	1	X-CH/1500KG/7M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	24.8	3
0170005-8	8717365096594	1.5	8	1	X-CH/1500KG/8M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	27	3
0170005-10	8717365096617	1.5	10	1	X-CH/1500KG/10M	7.1 x 21	5.0 x 23.7	360	30.8	170	158	29	42	360	31.4	3
0170007-3	8717365096273	2	3	1	X-CH/2000KG/3M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	20	3
0170007-6	8717365096280	2	6	1	X-CH/2000KG/6M	8.0 x 24	5.0 x 23.7	385	34.3	185	175	35	49	385	27.2	3
0170009-3	8717365096297	3	3	2	X-CH/3000KG/3M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	26	3
0170009-6	8717365096303	3	6	2	X-CH/3000KG/6M	7.1 x 21	5.0 x 23.7	510	34.3	220	158	37	50	510	36.2	3
0170011-3	8717365096310	5	3	2	X-CH/5000KG/3M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	41.5	3
0170011-6	8717365096327	5	6	2	X-CH/5000KG/6M	9.0 x 27	5.0 x 23.7	615	37.2	255	183	43	60	615	55	3
0170015-3	8717365096433	10	3	4	X-CH/10000KG/3M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	75	3
0170015-6	8717365096426	10	6	4	X-CH/10000KG/6M	9.0 x 27	5.0 x 23.7	820	40	360	183	47	65	820	99	3

Blueprint

