




Lever Hoist Elephant YII/250KG mini

Product information



The Elephant YII lever hoist is an extremely robust lever hoist for hoisting, pulling, tensioning and lashing in all directions. With one simple action the lever hoist can be set in its freewheel.

Features

- Very low self weight, compact dimensions.
- The rotatable top and bottom hook are provided with safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Self locked brake that holds the load at any desired height.
- Freewheel is possible in unloaded condition.
- Freewheel by one simple action.
- The hoist is fitted with a rubber anti-slip handle.
- Galvanized load chain (Grade 10).

Standard delivery

- 1,5 m lifting height (max distance between top and bottom hookpositions).

Option

- Available in other lifting heights.

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 13157

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Construction height mm	Hand force max. kg	A, B, C, D, E, F, H,	Weight kg	Delivery time
0208000-1.5	8717365259999	0.25	1.5	1	Y-II/250KG/1.5M	4.0 x 12	235	30	91 70 60 155 19 31 235	2.3	3
0208000-3	8717365264979	0.25	3	1	Y-II/250KG/3M	4.0 x 12	235	30	91 70 60 155 19 31 235	2.5	3
0208000-4.5	8717365264610	0.25	4.5	1	Y-II/250KG/4,5M	4.0 x 12	235	30	91 70 60 155 19 31 235	2.8	7
0208000-6	8717365264627	0.25	6	1	Y-II/250KG/6M	4.0 x 12	235	30	91 70 60 155 19 31 235	3	7

Blueprint

