



X-Line lever hoist

Product information



The Rema[®] X-Line lever hoist for safe and reliable operation during hoisting, pulling, tensioning or lashing.

Properties

- Low effort at full load.
- Increased operational safety due to double pawl system.
- Brake with asbestos free friction discs.
- Freewheel in unloaded condition.
- Load chain wheel is made of wear-resistant alloy steel.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 8).

Standard delivery

- 1,5 m lifting height (max distance between top and bottom hook).

Option

- Available in other lifting heights.



Marking: According to standard, CE-marked

Standard: EN 818-7, EN 13157

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg	Delivery time
0270000-1.5	8717365112522	0.25	1.5	1	X-LH/250KG/1,5M	4.0 x 12.0	235	28.2	100	70	86	163	20	31	235	2.5	7
0270000-3	8717365112485	0.25	3	1	X-LH/250KG/3M	4.0 x 12.0	235	28.2	100	70	86	163	20	31	235	3.1	7
0270000-4.5	8717365112492	0.25	4.5	1	X-LH/250KG/4,5M	4.0 x 12.0	235	28.2	100	70	86	163	20	31	235	3.7	7
0270000-6	8717365112508	0.25	6	1	X-LH/250KG/6M	4.0 x 12.0	235	28.2	100	70	86	163	20	31	235	4.3	7
0270001-1.5	8717365096358	0.5	1.5	1	X-LH/500KG/1,5M	5.0 x 15.0	310	24.8	150	90	118	253	22	32	310	5.5	7
0270001-3	8717365096860	0.5	3	1	X-LH/500KG/3M	5.0 x 15.0	310	24.8	150	90	118	253	22	32	310	6.4	7
0270001-4.5	8717365096877	0.5	4.5	1	X-LH/500KG/4,5M	5.0 x 15.0	310	24.8	150	90	118	253	22	32	310	7.3	7
0270001-6	8717365096884	0.5	6	1	X-LH/500KG/6M	5.0 x 15.0	310	24.8	150	90	118	253	22	32	310	8.2	7
0270003-1.5	8717365096365	0.8	1.5	1	X-LH/800KG/1,5M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	7.15	7
0270003-3	8717365096891	0.8	3	1	X-LH/800KG/3M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	8.2	7
0270003-4.5	8717365096907	0.8	4.5	1	X-LH/800KG/4,5M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	9.3	7
0270003-6	8717365096914	0.8	6	1	X-LH/800KG/6M	5.6 x 17.0	340	26.5	158	98	132	273	26	36	340	10.4	7
0270005-1.5	8717365096372	1.6	1.5	1	X-LH/1600KG/1,5M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	10.2	7
0270005-3	8717365096921	1.6	3	1	X-LH/1600KG/3M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	12	7
0270005-4.5	8717365096938	1.6	4.5	1	X-LH/1600KG/4,5M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	13.8	7
0270005-6	8717365096945	1.6	6	1	X-LH/1600KG/6M	7.1 x 21.0	400	29.5	185	111	145	378	29	43	400	15.6	7
0270007-1.5	8717365096389	3.2	1.5	1	X-LH/3200KG/1,5M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	22	7
0270007-3	8717365096952	3.2	3	1	X-LH/3200KG/3M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	25.5	7
0270007-4.5	8717365096969	3.2	4.5	1	X-LH/3200KG/4,5M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	29	7
0270007-6	8717365096976	3.2	6	1	X-LH/3200KG/6M	10.0 x 28.0	520	33.5	212	124	198	418	37	50	520	32.5	7
0270009-1.5	8717365096396	6.3	1.5	2	X-LH/6300KG/1,5M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	34	7
0270009-3	8717365096983	6.3	3	2	X-LH/6300KG/3M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	41	7

0270009-3	8717365096990	6.3	4.5	2	X-LH/6300KG/4,5M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	48	7
0270009-6	8717365097003	6.3	6	2	X-LH/6300KG/6M	10.0 x 28.0	640	37	212	124	230	418	43	53	640	55	7

Blueprint

