



## **REMA SELECT 30S adjustable trolley**

## Product information



The Rema Select 30 S spindle push trolley is suitable for various steel profiles. They are simple, quick and safe to install, ideal for assembly work.

## Properties

- Suitable for flat or bevel profiles.
- Equipped with solid steel wheels with maintenance-free bearings.
- Compact and light weight.
- Quick assembly through threaded adjustable.
- Safe by extra locking lever.
- With wheel rupture supports.
- Robust steel version with a low own weight.

Marking: According to standard, CE-marked Standard: EN 12100, EN 13157

| Part code | GTIN No.      | WLL<br>kg | Beam width | Model    | Minimum radius<br>mm | A mm | Bmin | Bmax | C mm | D<br>mm | E<br>mm | G<br>mm | Weight<br>kg | Delivery time |
|-----------|---------------|-----------|------------|----------|----------------------|------|------|------|------|---------|---------|---------|--------------|---------------|
| 0918001   | 8717365002915 | 500       | 64-203     | S30S-005 | 1,100                | 174  | 263  | 324  | 105  | 16      | 25.4    | 340     | 6            | 3             |
| 0918003   | 8717365002922 | 1,000     | 64-203     | S30S-010 | 1,100                | 174  | 263  | 324  | 105  | 16      | 25.4    | 340     | 7            | 3             |
| 0918005   | 8717365002939 | 2,000     | 76-203     | S30S-020 | 1,300                | 280  | 339  | 387  | 111  | 22      | 25.4    | 340     | 20           | 3             |
| 0918007   | 8717365002946 | 3,000     | 76-203     | S30S-030 | 1,400                | 345  | 374  | 438  | 127  | 27      | 26      | 345     | 32           | 3             |
| 0918009   | 8717365002953 | 5,000     | 100-305    | S30S-050 | 1,500                | 395  | 450  | 528  | 135  | 35      | 81      | 465     | 53           | 3             |

## Blueprint

