



REMA SELECT 30S adjustable trolley

Product information



The Rema Select 30 S spindle push trolley is suitable for various steel profiles. They are simple, quick and safe to install, ideal for assembly work.

Properties

- Suitable for flat or bevel profiles.
- Equipped with solid steel wheels with maintenance-free bearings.
- Compact and light weight.
- Quick assembly through threaded adjustable.
- Safe by extra locking lever.
- With wheel rupture supports.
- Robust steel version with a low own weight.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

| Part code | GTIN No. | WLL kg | Beam width mm | Model | Minimum radius mm | A mm | Bmin | Bmax | C mm | D mm | E mm | G mm | Weight kg | Delivery time |
|-----------|---------------|-----------|------------------|----------|----------------------|---------|------|------|---------|---------|---------|---------|--------------|---------------|
| 0918001 | 8717365002915 | 500 | 64-203 | S30S-005 | 1,100 | 174 | 263 | 324 | 105 | 16 | 25.4 | 340 | 6 | 7 |
| 0918003 | 8717365002922 | 1,000 | 64-203 | S30S-010 | 1,100 | 174 | 263 | 324 | 105 | 16 | 25.4 | 340 | 7 | 7 |
| 0918005 | 8717365002939 | 2,000 | 76-203 | S30S-020 | 1,300 | 280 | 339 | 387 | 111 | 22 | 25.4 | 340 | 20 | 3 |
| 0918007 | 8717365002946 | 3,000 | 76-203 | S30S-030 | 1,400 | 345 | 374 | 438 | 127 | 27 | 26 | 345 | 32 | 3 |
| 0918009 | 8717365002953 | 5,000 | 100-305 | S30S-050 | 1,500 | 395 | 450 | 528 | 135 | 35 | 81 | 465 | 53 | 3 |

Blueprint

