# REMA RMBT spindle beam trolley

**Product information**



**Properties**

- Suitable for flat or bevel profiles.
- Equipped with solid steel wheels with maintenance-free bearings.
- Compact and lightweight.
- Quick assembly through threaded adjustable.
- Safe by locking lever.
- With wheel rupture supports.

... *Read more*

**Marking:** According to standard, CE-mark
**Standard:** EN 12100, EN 13157


**REMA Hoisting & Lifting**
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA 75 YEARS HOISTING & LIFTING Work made easy.

# REMA RMBT spindle beam trolley

## Blueprint



## Technical data

| Part code | GTIN No. | WLL kg | Beam width mm | Model | A mm | B mm | C mm | D mm | E mm | G mm | H mm | J mm | K mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 0940002 | 8717365114786 | 2,000 | 76-203 | RMBT-2T | 272 | 176 | 360 | 54.5 | 72 | 16 | 8 | 21 | 95 | 7 |
| 0940003 | 8717365114793 | 3,000 | 76-203 | RMBT-3T | 381 | 270 | 475 | 82.5 | 118.5 | 25.5 | 14 | 33 | 113 | 25 |
| 0940006 | 8717365114809 | 6,000 | 105-305 | RMBT-6T | 429 | 356 | 560 | 125 | 116 | 26 | 16 | 34 | 100 | 52 |
| 0940010 | 8717365114816 | 10,000 | 160-305 | RMBT-10T | 541 | 430 | 630 | 145 | 119 | 32 | 16 | 41 | 110 | 74 |

REMA Hoisting & Lifting
info@rema.eu
+31433631777
© November 2026 - All Rights Reserved