

BLACK-LINE hand chain hoist

Product information





The Rema® BLACKLINE hand chain hoist is suitable for theater purposes where safety, ergonomics and a low operating force are paramount. The body and hooks are coloured black to limit visibility in sensitive dark environments.

Properties

- . Low operating effort at full load.
- Increased operational safety due to double pawl system.
- · Load pressure brake with astbestos free friction discs.
- Load chain wheel is made of wear-resistant alloy steel.
- Top and bottom hook have safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain (Grade 8).
- Galvanized hand chain.

Standard delivery

• Lifting height 10 or 15 meters

Option

- · Other lifting heights on request.
- Chain bucket for load chain up to 10 meters lifting height.

Norm:

• EN12100-1/2, EN13157, EN818-7



Marking: According to standard, CE-marked

Standard: EN 13157, EN 818-7

| Part code | GTIN No. | WLL Liftir kg | ng height Nur m | mber of falls | Model | Load chain mm | Hand chain mm | Construction height H | and force max. kg | A mm | B mm (| | D H V | Veight De | elivery time |
|--------------|---------------|------------------|--------------------|---------------|------------------------|------------------|------------------|-----------------------|----------------------|------|--------|----|--------|-----------|--------------|
| 0171000-10 8 | 3717365149962 | 250 | 10 | 1 | X-LINE/250KG/BLACK-10M | 4.0 x 12 | 5.0 x 23.7 | 280 | 23.5 | 108 | 106 | 20 | 30 280 | 6 | 3 |
| 0171000-15 8 | 3717365149979 | 250 | 15 | 1 | X-LINE/250KG/BLACK-15M | 4.0 x 12 | 5.0 x 23.7 | 280 | 23.5 | 108 | 106 | 20 | 30 280 | 6 | 3 |
| 0171001-10 8 | 3717365149986 | 500 | 10 | 2 | X-LINE/500KG/BLACK-10M | 5.0 x 15 | 5.0 x 23.7 | 280 | 24.9 | 130 | 128 | 22 | 34 280 | 9 | 3 |
| 0171001-15 8 | 3717365149993 | 500 | 15 | 2 | X-LINE/500KG/BLACK-15M | 5.0 x 15 | 5.0 x 23.7 | 280 | 24.9 | 130 | 128 | 22 | 34 280 | 9 | 3 |

Blueprint

