

1 leg REMA-10- RML-RCX-RCH

Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

1 leg REMA-10 | masterlink RML | connecting link RCX | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 1677-1, DIN 17115, DIN 5692, EN 818-7

Safety factor: 4

Grade: 10

1 leg REMA-10- RML-RCX-RCH

Technical data

| Part code | GTIN No. | Chain diameter mm | WLL ton | EWL m | Model | Weight kg |
|-------------|---------------|-------------------|---------|-------|--------------------------|-----------|
| 2691106-1 | 8717365150722 | 6 | 1.4 | 1 | 1400KG-6MM-RML-RCH-1M | 1.7 |
| 2691106-1.5 | 8717365150739 | 6 | 1.4 | 1.5 | 1400KG-6MM-RML-RCH-1,5M | 2.1 |
| 2691106-2 | 8717365150746 | 6 | 1.4 | 2 | 1400KG-6MM-RML-RCH-2M | 2.5 |
| 2691106-2.5 | 8717365150753 | 6 | 1.4 | 2.5 | 1400KG-6MM-RML-RCH-2,5M | 2.9 |
| 2691106-3 | 8717365150760 | 6 | 1.4 | 3 | 1400KG-6MM-RML-RCH-3M | 3.3 |
| 2691106-3.5 | 8717365150777 | 6 | 1.4 | 3.5 | 1400KG-6MM-RML-RCH-3,5M | 3.7 |
| 2691106-4 | 8717365150784 | 6 | 1.4 | 4 | 1400KG-6MM-RML-RCH-4M | 4.1 |
| 2691108-1 | 8717365150791 | 8 | 2.5 | 1 | 2500KG-8MM-RML-RCH-1M | 2.9 |
| 2691108-1.5 | 8717365150807 | 8 | 2.5 | 1.5 | 2500KG-8MM-RML-RCH-1,5M | 3.65 |
| 2691108-2 | 8717365150814 | 8 | 2.5 | 2 | 2500KG-8MM-RML-RCH-2M | 4.4 |
| 2691108-2.5 | 8717365150821 | 8 | 2.5 | 2.5 | 2500KG-8MM-RML-RCH-2,5M | 5.15 |
| 2691108-3 | 8717365150838 | 8 | 2.5 | 3 | 2500KG-8MM-RML-RCH-3M | 5.9 |
| 2691108-3.5 | 8717365150845 | 8 | 2.5 | 3.5 | 2500KG-8MM-RML-RCH-3,5M | 6.65 |
| 2691108-4 | 8717365150852 | 8 | 2.5 | 4 | 2500KG-8MM-RML-RCH-4M | 7.4 |
| 2691110-1 | 8717365150869 | 10 | 4 | 1 | 4000KG-10MM-RML-RCH-1M | 4.6 |
| 2691110-1.5 | 8717365150876 | 10 | 4 | 1.5 | 4000KG-10MM-RML-RCH-1,5M | 5.75 |
| 2691110-2 | 8717365150883 | 10 | 4 | 2 | 4000KG-10MM-RML-RCH-2M | 6.9 |
| 2691110-2.5 | 8717365150890 | 10 | 4 | 2.5 | 4000KG-10MM-RML-RCH-2,5M | 8.05 |
| 2691110-3 | 8717365150906 | 10 | 4 | 3 | 4000KG-10MM-RML-RCH-3M | 9.2 |
| 2691110-3.5 | 8717365150913 | 10 | 4 | 3.5 | 4000KG-10MM-RML-RCH-3,5M | 10.35 |
| 2691110-4 | 8717365150920 | 10 | 4 | 4 | 4000KG-10MM-RML-RCH-4M | 11.5 |
| 2691113-1 | 8717365150937 | 13 | 6.7 | 1 | 6700KG-13MM-RML-RCH-1M | 8.6 |
| 2691113-1.5 | 8717365150944 | 13 | 6.7 | 1.5 | 6700KG-13MM-RML-RCH-1,5M | 10.6 |
| 2691113-2 | 8717365150951 | 13 | 6.7 | 2 | 6700KG-13MM-RML-RCH-2M | 12.6 |
| 2691113-2.5 | 8717365150968 | 13 | 6.7 | 2.5 | 6700KG-13MM-RML-RCH-2,5M | 14.6 |
| 2691113-3 | 8717365150975 | 13 | 6.7 | 3 | 6700KG-13MM-RML-RCH-3M | 16.6 |
| 2691113-3.5 | 8717365150982 | 13 | 6.7 | 3.5 | 6700KG-13MM-RML-RCH-3,5M | 18.6 |
| 2691113-4 | 8717365150999 | 13 | 6.7 | 4 | 6700KG-13MM-RML-RCH-4M | 20.6 |
| 2691116-1 | 8717365151002 | 16 | 10 | 1 | 10T-16MM-RML-RCH-1M | 13.8 |
| 2691116-1.5 | 8717365151019 | 16 | 10 | 1.5 | 10T-16MM-RML-RCH-1,5M | 16.8 |
| 2691116-2 | 8717365151026 | 16 | 10 | 2 | 10T-16MM-RML-RCH-2M | 19.8 |

1 leg REMA-10- RML-RCX-RCH

Technical data

| Part code | GTIN No. | Chain diameter mm | WLL ton | EWL m | Model | Weight kg |
|-------------|---------------|----------------------|------------|----------|-----------------------|--------------|
| 2691116-2.5 | 8717365151033 | 16 | 10 | 2.5 | 10T-16MM-RML-RCH-2,5M | 22.8 |
| 2691116-3 | 8717365151040 | 16 | 10 | 3 | 10T-16MM-RML-RCH-3M | 25.8 |
| 2691116-3.5 | 8717365151057 | 16 | 10 | 3.5 | 10T-16MM-RML-RCH-3,5M | 28.8 |
| 2691116-4 | 8717365151064 | 16 | 10 | 4 | 10T-16MM-RML-RCH-4M | 31.8 |