

Chain sling assy 2-leg REMA-10-RML-RDG-RCS

Product information



REMA[®]

The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

2 leg REMA-10 chain | masterlink RML | clevis shortening hook RDG | self locking clevis hook RCS



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: DIN 17115, DIN 5692, EN 1677-1, EN 818-7

Safety factor: 4

Grade: 10

Chain sling assy 2-leg REMA-10-RML-RDG-RCS

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t	EWL m	Model	Weight kg
2692406-1	8717365153174	6	1.96	1.96	1,4	1	1960KG-6MM-RDG-RCS-1M	3.9
2692406-1.5	8717365153181	6	1.96	1.96	1,4	1.5	1960KG-6MM-RDG-RCS-1,5M	4.7
2692406-2	8717365153198	6	1.96	1.96	1,4	2	1960KG-6MM-RDG-RCS-2M	5.5
2692406-2.5	8717365153204	6	1.96	1.96	1,4	2.5	1960KG-6MM-RDG-RCS-2,5M	6.3
2692406-3	8717365153211	6	1.96	1.96	1,4	3	1960KG-6MM-RDG-RCS-3M	7.1
2692406-3.5	8717365153228	6	1.96	1.96	1,4	3.5	1960KG-6MM-RDG-RCS-3,5M	7.9
2692406-4	8717365153235	6	1.96	1.96	1,4	4	1960KG-6MM-RDG-RCS-4M	8.7
2692408-1	8717365153242	8	3.5	3.5	2,5	1	3500KG-8MM-RDG-RCS-1M	7
2692408-1.5	8717365153259	8	3.5	3.5	2,5	1.5	3500KG-8MM-RDG-RCS-1,5M	8.5
2692408-2	8717365153266	8	3.5	3.5	2,5	2	3500KG-8MM-RDG-RCS-2M	10
2692408-2.5	8717365153273	8	3.5	3.5	2,5	2.5	3500KG-8MM-RDG-RCS-2,5M	11.5
2692408-3	8717365153280	8	3.5	3.5	2,5	3	3500KG-8MM-RDG-RCS-3M	13
2692408-3.5	8717365153297	8	3.5	3.5	2,5	3.5	3500KG-8MM-RDG-RCS-3,5M	14.5
2692408-4	8717365153303	8	3.5	3.5	2,5	4	3500KG-8MM-RDG-RCS-4M	16
2692410-1	8717365153310	10	5.6	5.6	4	1	5600KG-10MM-RDG-RCS-1M	12.2
2692410-1.5	8717365153327	10	5.6	5.6	4	1.5	5600KG-10MM-RDG-RCS-1,5M	14.5
2692410-2	8717365153334	10	5.6	5.6	4	2	5600KG-10MM-RDG-RCS-2M	16.8
2692410-2.5	8717365153341	10	5.6	5.6	4	2.5	5600KG-10MM-RDG-RCS-2,5M	19.1
2692410-3	8717365153358	10	5.6	5.6	4	3	5600KG-10MM-RDG-RCS-3M	21.4
2692410-3.5	8717365153365	10	5.6	5.6	4	3.5	5600KG-10MM-RDG-RCS-3,5M	23.7
2692410-4	8717365153372	10	5.6	5.6	4	4	5600KG-10MM-RDG-RCS-4M	26
2692413-1	8717365153389	13	9.38	9.38	6,7	1	9380KG-13MM-RDG-RCS-1M	22.4
2692413-1.5	8717365153396	13	9.38	9.38	6,7	1.5	9380KG-13MM-RDG-RCS-1,5M	26.4
2692413-2	8717365153402	13	9.38	9.38	6,7	2	9380KG-13MM-RDG-RCS-2M	30.4
2692413-2.5	8717365153419	13	9.38	9.38	6,7	2.5	9380KG-13MM-RDG-RCS-2,5M	34.4
2692413-3	8717365153426	13	9.38	9.38	6,7	3	9380KG-13MM-RDG-RCS-3M	38.4
2692413-3.5	8717365153433	13	9.38	9.38	6,7	3.5	9380KG-13MM-RDG-RCS-3,5M	42.4
2692413-4	8717365153440	13	9.38	9.38	6,7	4	9380KG-13MM-RDG-RCS-4M	46.4
2692416-1	8717365153457	16	14	14	10	1	14T-16MM-RDG-RCS-1M	39.6
2692416-1.5	8717365153464	16	14	14	10	1.5	14T-16MM-RDG-RCS-1,5M	45.6
2692416-2	8717365153471	16	14	14	10	2	14T-16MM-RDG-RCS-2M	51.6

Chain sling assy 2-leg REMA-10-RML-RDG-RCS

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t	EWL m	Model	Weight kg
2692416-2.5	8717365153488	16	14	14	10	2.5	14T-16MM-RDG-RCS-2,5M	57.6
2692416-3	8717365153495	16	14	14	10	3	14T-16MM-RDG-RCS-3M	63.6
2692416-3.5	8717365153501	16	14	14	10	3.5	14T-16MM-RDG-RCS-3,5M	69.6
2692416-4	8717365153518	16	14	14	10	4	14T-16MM-RDG-RCS-4M	75.6