

Chain sling assy 3-leg REMA-10-RMA-RCX-RCH

Product information



REMA[®]

The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

3 leg REMA-10 | masterlink RMA | connecting link RCX | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality. [... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 17115, DIN 5692

Safety factor: 4

Grade: 10

Chain sling assy 3-leg REMA-10-RMA-RCX-RCH

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t	EWL m	Model	Weight kg
2693106-1	8717365153525	6	2.94	2.94	2,1	1	2940KG-6MM-RMA-RCH-1M	5
2693106-1.5	8717365153532	6	2.94	2.94	2,1	1.5	2940KG-6MM-RMA-RCH-1,5M	6.2
2693106-2	8717365153549	6	2.94	2.94	2,1	2	2940KG-6MM-RMA-RCH-2M	7.4
2693106-2.5	8717365153556	6	2.94	2.94	2,1	2.5	2940KG-6MM-RMA-RCH-2,5M	8.6
2693106-3	8717365153563	6	2.94	2.94	2,1	3	2940KG-6MM-RMA-RCH-3M	9.8
2693106-3.5	8717365153570	6	2.94	2.94	2,1	3.5	2940KG-6MM-RMA-RCH-3,5M	11
2693106-4	8717365153587	6	2.94	2.94	2,1	4	2940KG-6MM-RMA-RCH-4M	12.2
2693108-1	8717365153594	8	5.25	5.25	3,75	1	5250KG-8MM-RMA-RCH-1M	9.6
2693108-1.5	8717365153600	8	5.25	5.25	3,75	1.5	5250KG-8MM-RMA-RCH-1,5M	11.85
2693108-2	8717365153617	8	5.25	5.25	3,75	2	5250KG-8MM-RMA-RCH-2M	14.1
2693108-2.5	8717365153624	8	5.25	5.25	3,75	2.5	5250KG-8MM-RMA-RCH-2,5M	16.35
2693108-3	8717365153631	8	5.25	5.25	3,75	3	5250KG-8MM-RMA-RCH-3M	18.6
2693108-3.5	8717365153648	8	5.25	5.25	3,75	3.5	5250KG-8MM-RMA-RCH-3,5M	20.85
2693108-4	8717365153655	8	5.25	5.25	3,75	4	5250KG-8MM-RMA-RCH-4M	23.1
2693110-1	8717365153662	10	8.4	8.4	6	1	8400KG-10MM-RMA-RCH-1M	15
2693110-1.5	8717365153679	10	8.4	8.4	6	1.5	8400KG-10MM-RMA-RCH-1,5M	18.45
2693110-2	8717365153686	10	8.4	8.4	6	2	8400KG-10MM-RMA-RCH-2M	21.9
2693110-2.5	8717365153693	10	8.4	8.4	6	2.5	8400KG-10MM-RMA-RCH-2,5M	25.35
2693110-3	8717365153709	10	8.4	8.4	6	3	8400KG-10MM-RMA-RCH-3M	28.8
2693110-3.5	8717365153716	10	8.4	8.4	6	3.5	8400KG-10MM-RMA-RCH-3,5M	32.25
2693110-4	8717365153723	10	8.4	8.4	6	4	8400KG-10MM-RMA-RCH-4M	35.7
2693113-1	8717365153730	13	14	14	10,05	1	14T-13MM-RMA-RCH-1M	27.2
2693113-1.5	8717365153747	13	14	14	10,05	1.5	14T-13MM-RMA-RCH-1,5M	33.2
2693113-2	8717365153754	13	14	14	10,05	2	14T-13MM-RMA-RCH-2M	39.2
2693113-2.5	8717365153761	13	14	14	10,05	2.5	14T-13MM-RMA-RCH-2,5M	45.2
2693113-3	8717365153778	13	14	14	10,05	3	14T-13MM-RMA-RCH-3M	51.2
2693113-3.5	8717365153785	13	14	14	10,05	3.5	14T-13MM-RMA-RCH-3,5M	57.2
2693113-4	8717365153792	13	14	14	10,05	4	14T-13MM-RMA-RCH-4M	63.2
2693116-1	8717365153808	16	21	21	15	1	21T-16MM-RMA-RCH-1M	45.1
2693116-1.5	8717365153815	16	21	21	15	1.5	21T-16MM-RMA-RCH-1,5M	54.1
2693116-2	8717365153822	16	21	21	15	2	21T-16MM-RMA-RCH-2M	63.1

Chain sling assy 3-leg REMA-10-RMA-RCX-RCH

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t	EWL m	Model	Weight kg
2693116-2.5	8717365153839	16	21	21	15	2.5	21T-16MM-RMA-RCH-2,5M	72.1
2693116-3	8717365153846	16	21	21	15	3	21T-16MM-RMA-RCH-3M	81.1
2693116-3.5	8717365153853	16	21	21	15	3.5	21T-16MM-RMA-RCH-3,5M	90.1
2693116-4	8717365153860	16	21	21	15	4	21T-16MM-RMA-RCH-4M	99.1