



Chain sling assy 4-leg REMA-10-RMA-RCX-RCH

Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

4 leg REMA-10 | masterlink RMA | connecting link RCX | clevis sling hook RCH



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGVU](#), ensuring a testament to its exceptional quality.

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 1677-1, DIN 17115, DIN 5692

Safety factor: 4

Grade: 10

Part code	GTIN No.	Diameter mm	WLL	WLL 0-45° t	WLL 45-60° t	EWL	Model	Weight	Delivery time
2694106-1	8717365154928	6	2.94	2.94	2,1	1	2940KG-6MM-RMA-RCH-1M	6.2	7
2694106-1.5	8717365154935	6	2.94	2.94	2,1	1.5	2940KG-6MM-RMA-RCH-1,5M	7.8	7
2694106-2	8717365154942	6	2.94	2.94	2,1	2	2940KG-6MM-RMA-RCH-2M	9.4	7

2694106-2.5	8717365154959	6	2.94	2.94	2,1	2.5	2940KG-6MM-RMA-RCH-2,5M	11	7
2694106-3	8717365154966	6	2.94	2.94	2,1	3	2940KG-6MM-RMA-RCH-3M	12.6	7
2694106-3.5	8717365154973	6	2.94	2.94	2,1	3.5	2940KG-6MM-RMA-RCH-3,5M	14.2	7
2694106-4	8717365154980	6	2.94	2.94	2,1	4	2940KG-6MM-RMA-RCH-4M	15.8	7
2694108-1	8717365154997	8	5.25	5.25	3,75	1	5250KG-8MM-RMA-RCH-1M	12	7
2694108-1.5	8717365155000	8	5.25	5.25	3,75	1.5	5250KG-8MM-RMA-RCH-1,5M	15	7
2694108-2	8717365155017	8	5.25	5.25	3,75	2	5250KG-8MM-RMA-RCH-2M	18	7
2694108-2.5	8717365155024	8	5.25	5.25	3,75	2.5	5250KG-8MM-RMA-RCH-2,5M	21	7
2694108-3	8717365155031	8	5.25	5.25	3,75	3	5250KG-8MM-RMA-RCH-3M	24	7
2694108-3.5	8717365155048	8	5.25	5.25	3,75	3.5	5250KG-8MM-RMA-RCH-3,5M	27	7
2694108-4	8717365155055	8	5.25	5.25	3,75	4	5250KG-8MM-RMA-RCH-4M	30	7
2694110-1	8717365155062	10	8.4	8.4	6	1	8400KG-10MM-RMA-RCH-1M	18.8	7
2694110-1.5	8717365155079	10	8.4	8.4	6	1.5	8400KG-10MM-RMA-RCH-1,5M	23.4	7
2694110-2	8717365155086	10	8.4	8.4	6	2	8400KG-10MM-RMA-RCH-2M	28	7
2694110-2.5	8717365155093	10	8.4	8.4	6	2.5	8400KG-10MM-RMA-RCH-2,5M	32.6	7
2694110-3	8717365155109	10	8.4	8.4	6	3	8400KG-10MM-RMA-RCH-3M	37.2	7
2694110-3.5	8717365155116	10	8.4	8.4	6	3.5	8400KG-10MM-RMA-RCH-3,5M	41.8	7
2694110-4	8717365155123	10	8.4	8.4	6	4	8400KG-10MM-RMA-RCH-4M	46.4	7
2694113-1	8717365155130	13	14	14	10,05	1	14T-13MM-RMA-RCH-1M	30.2	7
2694113-1.5	8717365155147	13	14	14	10,05	1.5	14T-13MM-RMA-RCH-1,5M	38.2	7
2694113-2	8717365155154	13	14	14	10,05	2	14T-13MM-RMA-RCH-2M	46.2	7
2694113-2.5	8717365155161	13	14	14	10,05	2.5	14T-13MM-RMA-RCH-2,5M	54.2	7
2694113-3	8717365155178	13	14	14	10,05	3	14T-13MM-RMA-RCH-3M	62.2	7

2694113-3.5	8717365155185	13	14	14	10,05	3.5	14T-13MM-RMA-RCH-3,5M	70.2	7
2694113-4	8717365155192	13	14	14	10,05	4	14T-13MM-RMA-RCH-4M	78.2	7
2694116-1	8717365155208	16	21	21	15	1	21T-16MM-RMA-RCH-1M	56.5	7
2694116-1.5	8717365155215	16	21	21	15	1.5	21T-16MM-RMA-RCH-1,5M	68.5	7
2694116-2	8717365155222	16	21	21	15	2	21T-16MM-RMA-RCH-2M	80.5	7
2694116-2.5	8717365155239	16	21	21	15	2.5	21T-16MM-RMA-RCH-2,5M	92.5	7
2694116-3	8717365155246	16	21	21	15	3	21T-16MM-RMA-RCH-3M	104.5	7
2694116-3.5	8717365155253	16	21	21	15	3.5	21T-16MM-RMA-RCH-3,5M	116.5	7
2694116-4	8717365155260	16	21	21	15	4	21T-16MM-RMA-RCH-4M	128.5	7