



## Chain sling assy 4-leg REMA-10-RMA-RCX-RCS

### Product information



The [Rema® 10 assortment](#) offers versatile chain sling solutions, allowing you to easily create one, two, three, or four-legged chain sling assemblies. Each component is designed for durability and can be delivered and replaced individually when needed.

4 leg REMA-10 chain | masterlink RMA | connecting link RCX | self locking clevis hook RCS



Each component of this chain sling assembly carries the distinctive **H-84** mark certified by the [German DGUV](#), ensuring a testament to its exceptional quality.

**Marking:** According to standard, CE-marked

**Standard:** EN 818-7, EN 1677-1, DIN 17115, DIN 5692

**Safety factor:** 4

**Grade:** 10

Part code	GTIN No.	Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t	EWL m	Model	Weight kg	Delivery time
2694206-1	8717365155277	6	2.94	2.94	2,1	1	2940KG-6MM-RMA-RCS-1M	7	7
2694206-1.5	8717365155284	6	2.94	2.94	2,1	1.5	2940KG-6MM-RMA-RCS-1,5M	8.6	7
2694206-2	8717365155291	6	2.94	2.94	2,1	2	2940KG-6MM-RMA-RCS-2M	10.2	7

2694206-2.5	8717365155307	6	2.94	2.94	2,1	2.5	2940KG-6MM-RMA-RCS-2,5M	11.8	7
2694206-3	8717365155314	6	2.94	2.94	2,1	3	2940KG-6MM-RMA-RCS-3M	13.4	7
2694206-3.5	8717365155321	6	2.94	2.94	2,1	3.5	2940KG-6MM-RMA-RCS-3,5M	15	7
2694206-4	8717365155338	6	2.94	2.94	2,1	4	2940KG-6MM-RMA-RCS-4M	16.6	7
2694208-1	8717365155345	8	5.25	5.25	3,75	1	5250KG-8MM-RMA-RCS-1M	12.4	7
2694208-1.5	8717365155352	8	5.25	5.25	3,75	1.5	5250KG-8MM-RMA-RCS-1,5M	15.4	3
2694208-2	8717365155369	8	5.25	5.25	3,75	2	5250KG-8MM-RMA-RCS-2M	18.4	3
2694208-2.5	8717365155376	8	5.25	5.25	3,75	2.5	5250KG-8MM-RMA-RCS-2,5M	21.4	7
2694208-3	8717365155383	8	5.25	5.25	3,75	3	5250KG-8MM-RMA-RCS-3M	24.4	7
2694208-3.5	8717365155390	8	5.25	5.25	3,75	3.5	5250KG-8MM-RMA-RCS-3,5M	27.4	7
2694208-4	8717365155406	8	5.25	5.25	3,75	4	5250KG-8MM-RMA-RCS-4M	30.4	7
2694210-1	8717365155413	10	8.4	8.4	6	1	8400KG-10MM-RMA-RCS-1M	19.6	7
2694210-1.5	8717365155420	10	8.4	8.4	6	1.5	8400KG-10MM-RMA-RCS-1,5M	24.2	7
2694210-2	8717365155437	10	8.4	8.4	6	2	8400KG-10MM-RMA-RCS-2M	28.8	7
2694210-2.5	8717365155444	10	8.4	8.4	6	2.5	8400KG-10MM-RMA-RCS-2,5M	33.4	7
2694210-3	8717365155451	10	8.4	8.4	6	3	8400KG-10MM-RMA-RCS-3M	38	7
2694210-3.5	8717365155468	10	8.4	8.4	6	3.5	8400KG-10MM-RMA-RCS-3,5M	42.6	7
2694210-4	8717365155475	10	8.4	8.4	6	4	8400KG-10MM-RMA-RCS-4M	47.2	7
2694213-1	8717365155482	13	14	14	10,05	1	14T-13MM-RMA-RCS-1M	37	7
2694213-1.5	8717365155499	13	14	14	10,05	1.5	14T-13MM-RMA-RCS-1,5M	45	7
2694213-2	8717365155505	13	14	14	10,05	2	14T-13MM-RMA-RCS-2M	53	3
2694213-2.5	8717365155512	13	14	14	10,05	2.5	14T-13MM-RMA-RCS-2,5M	61	7
2694213-3	8717365155529	13	14	14	10,05	3	14T-13MM-RMA-RCS-3M	69	7

2694213-3.5	8717365155536	13	14	14	10,05	3.5	14T-13MM-RMA-RCS-3,5M	77	7
2694213-4	8717365155543	13	14	14	10,05	4	14T-13MM-RMA-RCS-4M	85	7
2694216-1	8717365155550	16	21	21	15	1	21T-16MM-RMA-RCS-1M	63.3	7
2694216-1.5	8717365155567	16	21	21	15	1.5	21T-16MM-RMA-RCS-1,5M	75.3	7
2694216-2	8717365155574	16	21	21	15	2	21T-16MM-RMA-RCS-2M	87.3	7
2694216-2.5	8717365155581	16	21	21	15	2.5	21T-16MM-RMA-RCS-2,5M	99.3	7
2694216-3	8717365155598	16	21	21	15	3	21T-16MM-RMA-RCS-3M	111.3	7
2694216-3.5	8717365155604	16	21	21	15	3.5	21T-16MM-RMA-RCS-3,5M	123.3	7
2694216-4	8717365155611	16	21	21	15	4	21T-16MM-RMA-RCS-4M	135.3	7