

## Dynamometer 05

### Product information



### Mechanical properties

- Aluminum housing.
- Alloy steel pulling unit.
- Test load 2 x WLL (without losing accuracy).
- Safety factor 5 x WLL.
- International Protection Rating / Ingress Protection: IP65 (EN60529).

### Electrical specifications

- Alkaline battery (3 x AA type).
- Battery operating time about 180 hours.

### Electronic specifications

- Operating temperature range between -5° C to + 55° C.
- Accuracy up to approx. 0.1% of the reading value.
- Battery indicator.

### Option

- U-13 Unilock bow schackle (2635013).

... [Read more](#)

**Marking:** According to standard, CE-marked


**Standard:** EN 12100, EN 13155, EN 13889

**Note:** Includes plastic case, manual and calibration report.

**Safety factor:** 5

# Dynamometer 05

## Blueprint



## Technical data

Part code	GTIN No.	WLL ton	Model	Shackle	Resolution kg	A mm	B mm	C mm	D mm	E mm	F mm	Weight kg
1514001	8717365111983	0.6	DSD05-0.6T	U-13 ex.	0.2	170	16	21	-	-	-	2.3
1514003	8717365111990	1	DSD05-1.0T	U-13 ex.	0.5	170	16	21	-	-	-	2.3