



Dynamometer 05T with remote control

Product information



Mechanical properties

- Aluminum housing.
- Alloy steel pulling unit.
- Test load 2 x WLL (without losing accuracy).
- Safety factor 5 x WLL.
- International Protection Rating / Ingress Protection: IP65 (EN60529).

Electrical specifications

- Alkaline battery (3 x AA type).
- Battery operating time about 180 hours.

Electronic specifications

- Operating temperature range between -5 ° C to + 55 ° C.
- Accuracy up to approx. 0.1% of the reading value.
- Battery indicator.

Standard delivery

- Bow shackles (3,2T and 6,3T).
- Remote control to tare.

Option

- Bow shackle from 10T.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13155, EN 13889

Note: Includes plastic case, manual and calibration report.

Safety factor: 5

| Part code | GTIN No. | WLL ton | Model | Shackle | Resolution kg | A mm | B mm | C mm | D mm | E mm | F mm | Weight kg | Delivery time |
|-----------|---------------|------------|--------------|-----------|------------------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 1514005 | 8717365110986 | 3.2 | DSD05T-3.2T | 3,25t in. | 1 | 199 | 69 | 130 | 25 | 269 | 20 | 4.7 | 7 |
| 1514007 | 8717365110993 | 6.3 | DSD05T-6.3T | 6,5t in. | 2 | 213 | 69 | 144 | 35 | 348 | 26 | 7 | 3 |
| 1514009 | 8717365112003 | 10 | DSD05T-10.0T | 12t ex. | 5 | 265 | 100 | 181 | 50 | 455 | 36 | 9.6 | 3 |

Blueprint

