



TEO Mechanical crane scale

Product information

REMA[®]

The REMA TEO mechanical crane scale with one suspension eye and hook with safety latch up to 5,000 kg and from 12,500 kg up to 85,000 kg with 2 eyes.

Properties

- Very robust design.
- Low self weight.
- Plexiglas with rubber edge protects the display.
- Accuracy within 1% of the full reading.
- Very easy trimming for zero adjustment.
- Safety factor 5 (safety factor 4 from TEO-5000).

Options

- Distance reading.
- Bow shackle.

Marking: According to standard, CE-marked

Standard: EN 13155, EN 12100

| Part Code | GTIN No. | WLL ton | Model | Resolution kg | A mm | B mm | C mm | D mm | E mm | Weight kg |
|-----------|---------------|---------|------------|---------------|------|------|------|------|------|-----------|
| 1550001 | 8717365007606 | 0.2 | TEO-200 | 1 | 60 | 53 | 230 | 27 | 35 | 5 |
| 1550003 | 8717365007613 | 0.32 | TEO-320 | 2 | 60 | 53 | 230 | 27 | 35 | 5 |
| 1550005 | 8717365007620 | 0.5 | TEO-500 | 2 | 60 | 53 | 230 | 27 | 35 | 5 |
| 1550007 | 8717365007637 | 0.75 | TEO-750 | 5 | 60 | 53 | 230 | 27 | 35 | 5 |
| 1550009 | 8717365007644 | 1.25 | TEO-1250 | 5 | 60 | 53 | 230 | 27 | 35 | 5 |
| 1550011 | 8717365007651 | 2 | TEO-2000 | 10 | 60 | 53 | 230 | 27 | 35 | 5 |
| 1550013 | 8717365007668 | 3.2 | TEO-3200 | 20 | 75 | 53 | 280 | 34 | 46 | 5.5 |
| 1550015 | 8717365007675 | 5 | TEO-5000 | 20 | 75 | 53 | 300 | 42 | 56 | 6.5 |
| 1550017 | 8717365007682 | 12.5 | TEO-12.500 | 50 | 40 | 41 | 213 | - | - | 8.1 |
| 1550019 | 8717365007699 | 25 | TEO-25.000 | 100 | 55 | 42 | 267 | - | - | 12.9 |
| 1550021 | 8717365007705 | 50 | TEO-50.000 | 200 | 75 | 56 | 329 | - | - | 25 |
| 1550023 | 8717365007712 | 85 | TEO-85.000 | 500 | 85 | 60 | 390 | - | - | 60 |

Blueprint

