Eye nut type C-15E DIN-582

Product information



The safe working load is only suitable for hoisting and pulling in line.
The lifting eye must not be loaded sideways.

... *Read more*

Material: C-15
Marking: According to standard, CE-marked
Standard: DIN 582
Note: Only use in a straight lifting position.


REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA 75 YEARS HOISTING & LIFTING Work made easy.

Eye nut type C-15E DIN-582

Blueprint



Technical data

Part code	Code	WLL ton	Model	D2 mm	D3 mm	D4mm mm	E mm	H mm	M mm	Weight kg
3017101	8717365183669	0.14	DIN582-C15E-M8-140KG	20	36	20	8.5	36	8	0.06
3017103	8717365183676	0.23	DIN582-C15E-M10-230KG	25	45	25	10	45	10	0.1
3017105	8717365183683	0.34	DIN582-C15E-M12-340KG	30	54	30	11	53	12	0.16
3017107	8717365183690	0.49	DIN582-C15E-M14-490KG	35	63	35	13	62	14	0.24
3017109	8717365183706	0.7	DIN582-C15E-M16-700KG	35	63	35	13	62	16	0.4
3017111	8717365183713	1.2	DIN582-C15E-M20-1200KG	40	72	40	16	71	20	0.36
3017113	8717365183720	1.8	DIN582-C15E-M24-1800KG	50	90	50	20	90	24	0.71
3017115	8717365183737	2.5	DIN582-C15E-M27-2500KG	50	90	50	20	90	27	1.1
3017117	8717365183744	3.2	DIN582-C15E-M30-3200KG	65	108	60	25	109	30	1.32
3017119	8717365183751	4.6	DIN582-C15E-M36-4600KG	75	126	70	30	128	36	2.08

REMA Hoisting & Lifting
info@rema.eu
+31433631777
© November 2026 - All Rights Reserved