



C810FX lifting points (G10)

Product information

CARTEC

Features: Tighten hand-tight in load direction.

Marking: According to standard, CE-marked

Standard: EN 1677-1

Note: Rotatable through 360°.

Warning: Not rotatable under load.

Safety factor: 4

Grade: 10

| Part code | Code | WLL ton | Thread mm | Model | A | B mm | C mm | D mm | E mm | F mm | M x L mm | K mm | SW mm | Weight kg | Delivery time |
|-----------|---------------|---------|-----------|------------------|------|------|------|------|------|------|------------|------|-------|-----------|---------------|
| 2611508 | 8717365115127 | 0.3 | M8 | C810FX-M8-0.3T | 44.5 | 8 | 10 | 29 | 32 | 23 | M8 x 21.5 | 45 | 13 | 0.17 | 3 |
| 2611510 | 8717365115134 | 0.4 | M10 | C810FX-M10-0.4T | 44.5 | 8 | 10 | 29 | 32 | 23 | M10 x 21.5 | 45 | 14 | 0.2 | 3 |
| 2611512 | 8717365115141 | 0.75 | M12 | C810FX-M12-0.75T | 53.5 | 11 | 11 | 34 | 44 | 27 | M12 x 26.5 | 56 | 16 | 0.39 | 3 |
| 2611516 | 8717365115158 | 1.5 | M16 | C810FX-M16-1.5T | 59.5 | 13 | 14.5 | 39 | 56 | 29 | M16 x 30.5 | 65 | 21 | 0.69 | 3 |
| 2611520 | 8717365115165 | 2.3 | M20 | C810FX-M20-2.3T | 67 | 14 | 17 | 42 | 58 | 34 | M20 x 33.0 | 70 | 26 | 0.71 | 7 |
| 2611524 | 8717365115172 | 3.2 | M24 | C810FX-M24-3.2T | 80 | 18 | 19 | 52 | 73 | 40 | M24 x 40.0 | 30 | 30 | 1.7 | 7 |
| 2611530 | 8717365115189 | 4.5 | M30 | C810FX-M30-4.5T | 101 | 22 | 27 | 62 | 80 | 50 | M30 x 51.0 | 106 | 36 | 2.44 | 3 |

Blueprint

