REMA 75 YEARS HOISTING & LIFTING Work made easy.

Bow shackle with screwpin G-4161

Product information



Galvanized steel with a high tensile strength suitable for temperatures between -20 ° C and + 200 ° C. Equipped with screwpin.

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 13889

Safety factor: 6
Grade: 6


REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA 75 YEARS HOISTING & LIFTING Work made easy.

Bow shackle with screwpin G-4161

Blueprint



Technical data

Part code	Code	WLL ton	Model	A mm	B mm	C mm	D mm	E mm	Weight kg
3011001	8717365013331	0.5	G4161-1/4	7	8	12	29	20	0.06
3011003	8717365013348	0.75	G4161-5/16	9	10	13.5	32	21	0.11
3011005	8717365013355	1	G4161-3/8	10	11	16.1	36	26	0.15
3011007	8717365013362	1.5	G4161-7/16	11	13	18	43	29	0.21
3011009	8717365013379	2	G4161-1/2	13,5	16	22	51	32	0.37
3011011	8717365013386	3.25	G4161-5/8	16	19	27	64	43	0.65
3011013	8717365013393	4.75	G4161-3/4	19	22	31	76	51	1.06
3011015	8717365013409	6.5	G4161-7/8	22	25	36	83	58	1.56
3011017	8717365013416	8.5	G4161-1	25	28	43	95	68	2.32
3011018	8717365013423	9.5	G4161-1.1/8	28	32	47	108	75	3.28
3011019	8717365013430	12	G4161-1.1/4	32	35	51	115	83	4.51
3011020	8717365013447	13.5	G4161-1.3/8	35	38	57	133	92	5.93
3011021	8717365013454	17	G4161-1.1/2	38	42	60	146	99	7.89
3011023	8717365013461	25	G4161-1.3/4	45	50	74	178	126	13.4
3011025	8717365022968	35	G4161-2	50	57	83	197	138	18.15
3011027	8717365258541	42.5	G4161-2.1/4	57	65	95	222	160	26.29
3011029	8717365023583	55	G4161-2.1/2	65	70	105	260	180	37.6

REMA Hoisting & Lifting
info@rema.eu
+31433631777
© November 2026 - All Rights Reserved