REMA 75 YEARS HOISTING & LIFTING Work made easy.

D-shackle with nut-bolt secured by split pin type G-4153

Product information



Galvanized steel with a high tensile strength suitable for temperatures between -20 ° C and + 200 ° C. Equipped with nut-bolt secured by split pin

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 13889

Safety factor: 6
Grade: 6

REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA 75 YEARS HOISTING & LIFTING Work made easy.

D-shackle with nut-bolt secured by split pin type G-4153

Blueprint



Technical data

Part code	Code	WLL ton	Model	A mm	B mm	C mm	D mm	Weight kg
3014009	8717365013751	2	G4153-1/2	13	16	22	43	0.37
3014011	8717365013768	3.25	G4153-5/8	16	19	27	51	0.65
3014013	8717365013775	4.75	G4153-3/4	19	22	31	59	1.06
3014015	8717365013782	6.5	G4153-7/8	22	25	36	73	1.56
3014017	8717365013799	8.5	G4153-1	25	28	43	85	2.32
3014019	8717365013805	9.5	G4153-1.1/8	28	32	47	90	3.28
3014021	8717365013812	12	G4153-1.1/4	32	35	51	94	4.51
3014023	8717365013829	13.5	G4153-1.3/8	35	38	57	115	5.93
3014025	8717365013836	17	G4153-1.1/2	38	42	60	127	7.89
3014027	8717365013843	25	G4153-1.3/4	45	50	74	149	13.4
3014029	8717365022999	35	G4153-2	50	57	83	171	16.86
3014031	8717365025792	42.5	G4153-2.1/4	57	65	95	190	24.56
3014033	8717365025808	55	G4153-2.1/2	65	70	105	203	32.65

REMA Hoisting & Lifting
info@rema.eu
+31433631777
© November 2026 - All Rights Reserved