



D-shackle with screwpin type G-4151

Product information

Galvanized steel with a high tensile strength suitable for temperatures between -20 ° C and + 200 ° C. Equipped with screwpin.

Marking: According to standard, CE-marked

Standard: EN 13889

Safety factor: 6

Grade: 6

Part code	Code	WLL ton	Model	A,	B,	C,	D,	Weight kg	Delivery time
3013001	8717365013614	0.5	G4151-1/4	7	8	12	25	0.06	3
3013003	8717365013621	0.75	G4151-5/16	9	10	13.5	27	0.11	3
3013005	8717365013638	1	G4151-3/8	10	11	16.1	31	0.16	3
3013007	8717365013645	1.5	G4151-7/16	11	13	18	37	0.21	3
3013009	8717365013652	2	G4151-1/2	13,5	16	22	43	0.37	3
3013011	8717365013669	3.25	G4151-5/8	16	19	27	51	0.65	3
3013013	8717365013676	4.75	G4151-3/4	19	22	31	59	1.06	3
3013015	8717365013683	6.5	G4151-7/8	22	25	36	73	1.56	3
3013017	8717365013690	8.5	G4151-1	25	28	43	85	2.32	3
3013019	8717365013706	9.5	G4151-1.1/8	28	32	47	90	3.28	3
3013021	8717365013713	12	G4151-1.1/4	32	35	51	94	4.51	3
3013023	8717365013720	13.5	G4151-1.3/8	35	38	57	115	5.93	3
3013025	8717365013737	17	G4151-1.1/2	38	42	60	127	7.89	3
3013027	8717365013744	25	G4151-1.3/4	45	50	74	149	13.4	3
3013029	8717365025761	35	G4151-2	50	57	83	171	16.86	7
3013031	8717365025778	42.5	G4151-2.1/4	57	65	95	190	24.56	7
3013033	8717365025785	55	G4151-2.1/2	65	70	105	203	32.65	7

Blueprint

