



## CBU Lightweight Holland profile (Hp) clamp for universal lifting

### Product information



Specifically developed for lifting and transportation HP profiles and ship constructions using HP profiles. Fitted with 2 cams and universal lifting eyes.

#### Application

- For vertical lifting, handling and transporting of Holland Profile (HP) shipbuilding structures from all positions
- Jaw openings available from: 0 to 45 mm
- Higher WLL available upon request.
- Lifting of longer sections should be performed with a spreader beam fitted with multiple clamps.

**Marking:** According to standard, CE-marked

**Standard:** EN 13155, EN 12100

**Warning:** Min . WLL is 10% of max . WLL.

**Safety factor:** 5

| Part code | GTIN No.      | WLL ton | Jaw width mm | Model   | A mm | B mm | C mm | D mm | E mm | F mm | Weight kg | Delivery time |
|-----------|---------------|---------|--------------|---------|------|------|------|------|------|------|-----------|---------------|
| 3310001   | 8717365015083 | 3       | 0-35         | CBU-3.0 | 90   | 70   | 370  | 185  | 55   | 54   | 8         | 7             |
| 3310003   | 8717365015090 | 5       | 0-45         | CBU-5.0 | 110  | 70   | 435  | 225  | 60   | 86   | 17.3      | 7             |

Blueprint

