



## CBU Lightweight Holland profile (Hp) clamp for universal lifting

### Product information



Specifically developed for lifting and transportation HP profiles and ship constructions using HP profiles. Fitted with 2 cams and universal lifting eyes.

#### Application

- For vertical lifting, handling and transporting of Holland Profile (HP) shipbuilding structures from all positions
- Jaw openings available from: 0 to 45 mm
- Higher WLL available upon request.
- Lifting of longer sections should be performed with a spreader beam fitted with multiple clamps.

**Marking:** According to standard, CE-marked

**Standard:** EN 13155, EN 12100

**Warning:** Min . WLL is 10% of max . WLL.

**Safety factor:** 5

| Part code | GTIN No.      | WLL<br>ton | Jaw width<br>mm | Model   | A mm | B mm | C mm | D<br>mm | E<br>mm | F<br>mm | Weight<br>kg | Delivery time |
|-----------|---------------|------------|-----------------|---------|------|------|------|---------|---------|---------|--------------|---------------|
| 3310001   | 8717365015083 | 3          | 0-35            | CBU-3.0 | 90   | 70   | 370  | 185     | 55      | 54      | 8            | 7             |
| 3310003   | 8717365015090 | 5          | 0-45            | CBU-5.0 | 110  | 70   | 435  | 225     | 60      | 86      | 17.3         | 7             |

## Blueprint

