REMA 75 YEARS HOISTING & LIFTING Work made easy.

CPH pipe lifting hooks

Product information



REMA

Properties

- Jaw is covered with a special high quality pressure resistant plastic.
- These hooks must always be used in pairs.

Application

- For horizontal lifting and transporting of steel and concrete pipes without damaging the product.

... *Read more*

Features: WLL = per pair
Marking: According to standard, CE-mark
Standard: EN 13155, EN 12100
Note: Exclusive fasteners.


REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA 75 YEARS HOISTING & LIFTING Work made easy.

CPH pipe lifting hooks

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	O mm	X mm	Weight kg/pair
3313025	8717365015304	1.5	40	CPH-1.5	120	32	185	70	41	16	40	23	3.2
3313027	8717365015311	3	40	CPH-3.0	120	32	185	70	41	16	40	23	3.2
3313029	8717365015328	4	50	CPH-4.0	140	58	180	70	41	26	50	23	6
3313031	8717365015335	6	50	CPH-6.0	140	58	180	70	41	26	50	23	6
3313033	8717365015342	8	70	CPH-8.0	140	58	200	70	45	26	70	25	7.2
3313034	8717365023590	10	70	CPH-10.0	140	58	200	70	86	26	70	44	10
3313035	8717365258725	12	70	CPH-12.0	140	58	200	70	86	26	70	44	12
3313037	8717365258732	15	70	CPH-15.0	155	75	250	70	100	26	70	59	18
3313039	8717365258749	20	70	CPH-20.0	155	75	250	70	100	26	70	59	20

REMA Hoisting & Lifting
info@rema.eu
+31433631777
© November 2026 - All Rights Reserved