REMA 75 YEARS HOISTING & LIFTING Work made easy.

CRK tube lifting clamps

Product information



REMA

Properties

- The clamp is locked in the open position.
- To perform lifting, the operator must lift the handle while the force on the lifting eye is being applied.
- When laying down the load, the clamp automatically opens.

Application

- For horizontal lifting and transporting of tubes, pipes, tube bundles, rolls and other solid round materials.

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 12100, EN 13155


REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA® 75 YEARS HOISTING & LIFTING Work made easy.

CRK tube lifting clamps

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Jaw width mm	Model	O mm	A mm	B min-maxmm mm	D mm	G mm	Weight kg
3311001	8717365015106	0.5	49-114	CRK-0.5	49-114	300-400	146-207	47	45	4.5
3311003	8717365015113	1	114-219	CRK-1.0	114-219	430-615	110-170	47	45	9
3311005	8717365015120	2	219-368	CRK-2.0	219-368	670-955	225-320	56	65	31
3311007	8717365015137	3	368-508	CRK-3.0	368-508	875-1165	590-710	56	65	39

REMA Hoisting & Lifting
info@rema.eu
+31433631777
© November 2026 - All Rights Reserved