REMA® 75 YEARS HOISTING & LIFTING Work made easy.

CS-H vertical plate lifting clamps for plate till 50RC (485 HB)

Product information



REMA®

Lifting clamps for safely transporting steel plates in vertical position.

Properties

- Equipped with standard lifting eye, movable in one direction.
- Always equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when load is being lowered.
- WLL and size of the jaw opening are clearly indicated on the clamp.
- Safety factor of at least 5 x WLL.
- Each clamp is 2x WLL testloaded.

Application

- For lifting steel plates up to a hardness of 50 RC (485 HB).
- Suitable for lifting, 180 ° turning and vertical transport of steel plates

... *Read more*

Marking: According to standard, CE-mark
Standard: EN 12100, EN 13155
Note: Minimum weight to be lifted is 10% of the safe workload.

Safety factor: 5


REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA 75 YEARS HOISTING & LIFTING Work made easy.

CS-H vertical plate lifting clamps for plate till 50RC (485 HB)

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg
3361101	8717365024658	0.75	0-13	CS-0.75H	47	30	205	100	35	37	10	1.5
3361103	8717365024665	1	0-25	CS-1.0H	55	45	265	142	38	47	15	3.6
3361105	8717365024672	2	0-35	CS-2.0H	80	65	335	185	55	56	17	6.5
3361107	8717365024689	3	0-35	CS-3.0H	80	65	335	185	55	56	17	7
3361109	8717365024696	4	0-45	CS-4.5H	85	70	430	230	60	77	20	16
3361111	8717365024702	6	0-32	CS-6.0H	114	75	490	230	78	78	20	19

REMA Hoisting & Lifting
info@rema.eu
+31433631777
© November 2026 - All Rights Reserved