REMA 75 YEARS HOISTING & LIFTING Work made easy.

KSB spindle beam clamps

Product information



For safe lifting and moving of steel beams or as a fixed suspension point.

Properties

- Low constructional height.
- Easy mounting due to the spindle.
- Suitable for both IPE or INP steel beams.

... *Read more*

Marking: CE-mark

Safety factor: 4


REMA Hoisting & Lifting
info@rema.eu
+31433631777

© November 2026 - All Rights Reserved

REMA 75 YEARS HOISTING & LIFTING Work made easy.

KSB spindle beam clamps

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Beam width mm	Model	A max mm	B max mm	B min mm	C mm	D mm	E mm	F max mm	F min mm	G mm	H mm	J mm	Weight kg
3317001	8717365015540	1	80-240	KSB-1	270	370	183	94	4	198	154	100	22	20	20	3.5
3317002	8717365015557	2	80-240	KSB-2	270	370	183	102	6	198	154	100	22	20	20	4.5
3317003	8717365015564	3	90-330	KSB-3	355	500	243	132	8	263	219	148	46	22	38	9.5
3317005	8717365015571	5	90-330	KSB-5	355	500	243	142	10	263	219	148	43	28	38	11
3317010	8717365015588	10	90-350	KSB-10	364	521	269	180	12	285	239	165	51	38	38	18

REMA Hoisting & Lifting
info@rema.eu
+31433631777
© November 2026 - All Rights Reserved