



## KSBO spindle beam clamps with eye

### Product information



For lifting and transportation of beams or as fixed suspension points.

#### Properties

- Equipped with suspension eye.
- **Locking spindle can be secured by means of a nut for extra safety.**
- Easy assembly by spindle.
- Suitable for IPE and INP bars.

**Marking:** According to standard, CE-marked

**Standard:** EN 12100, EN 13155

**Safety factor:** 4

Part code	GTIN No.	WLL ton	Beam width	Model	A max mm	B min mm	B max mm	C mm	D mm	E mm	F max mm	F min mm	G mm	H mm	K mm	Weight kg	Delivery time
3317101	8717365114595	1	80-245	KSBO-1	270	183	370	94	4	218	100	154	18	28	43	4	3
3317102	8717365114601	2	80-245	KSBO-2	270	183	370	102	6	218	100	154	18	28	43	5	3
3317103	8717365114618	3	90-330	KSBO-3	355	243	500	132	8	276	148	219	40	43	60	10	3
3317105	8717365114625	5	90-330	KSBO-5	355	243	500	142	10	276	148	219	40	43	60	12	3
3317110	8717365114632	10	90-340	KSBO-10	364	269	521	180	12	301	165	239	47	62	91	18.5	3

# Blueprint

