



Superclamp A-serie

Product information



Hinged hand trolley with automatic locking.

Properties

- Can be mounted on rails easily and very quickly.
- With wheel fracture support device.
- Maximum beam thickness for type A1=28 mm and A2/A3 = 30 mm.

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

| Part code | GTIN No. | WLL ton | Beam width mm mm | Jaw width mm | Model | A mm | B mm | C mm | D mm | E mm | G mm | H mm | J mm | K mm | Weight kg | Delivery time |
|-----------|---------------|---------|------------------|--------------|-------|------|------|------|------|------|---------|------|------|------|-----------|---------------|
| 3512001 | 8717365017179 | 3 | 76-230 | | A1 | 380 | 280 | 110 | 250 | 170 | 76-230 | 82 | 30 | 32 | 21 | 7 |
| 3512003 | 8717365017186 | 6 | 100-305 | | A2 | 500 | 296 | 110 | 290 | 170 | 100-305 | 88 | 40 | 38 | 33 | 7 |
| 3512005 | 8717365017193 | 10 | 100-305 | | A3 | 580 | 290 | 135 | 310 | 170 | 100-305 | 109 | 40 | 38 | 47.5 | 7 |

Blueprint

