



Portal crane REMA PKA, Aluminum

Product information



Properties

- Very short assembly and disassembly time of a few minutes.
- 3-part dismantlable, two columns and a support beam.
- Foldable columns for easy transport.
- Height adjustment, installation in low spaces is possible.
- Adjustable span by one, movable, columns.
- Very low own weight because the crane is made entirely of aluminum and plastic.

Applications

- If a non-permanent lifting point has to be created quickly and easily.
- Ideal for use when changing tools on machines or as an aid for repairs and replacement of parts, machines and pumps.

Standard delivery

- Trolley included.
- Exclusive hoist (see Chapter 1).

Option

- Wall console for 1 side.
- Mobile version (no load).
- Other versions on request.

Material: Aluminium

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157, EN 15011

| Part code | GTIN No. | WLL ton | Height m m | Model | Width mm | Main beam length mm | Weight kg | Delivery time |
|-----------|---------------|---------|------------|---------|----------|---------------------|-----------|---------------|
| 3940008 | 8717365023286 | 1.5 | 1.18-2.1 | PKA-K-2 | 1,200 | 2,000 | 98 | 7 |
| 3940000 | 8717365020155 | 1.5 | 1.18-2.1 | PKA-K-3 | 1,200 | 3,000 | 105 | 7 |
| 3940009 | 8717365023293 | 1.5 | 1.68-3 | PKA-M-2 | 1,710 | 2,000 | 111 | 7 |
| 3940001 | 8717365020162 | 1.5 | 1.18-2.1 | PKA-K-4 | 1,200 | 4,000 | 115 | 3 |
| 3940002 | 8717365020179 | 1.5 | 1.68-3 | PKA-M-3 | 1,710 | 3,000 | 121 | 7 |
| 3940010 | 8717365023309 | 1.5 | 2.23-4 | PKA-G-2 | 2,290 | 2,000 | 127 | 7 |
| 3940003 | 8717365020186 | 1.5 | 1.68-3 | PKA-M-4 | 1,710 | 4,000 | 130 | 7 |
| 3940004 | 8717365020193 | 1.5 | 2.23-4 | PKA-G-3 | 2,290 | 3,000 | 138 | 7 |
| 3940007 | 8717365259760 | 1.5 | 1.68-3 | PKA-M-5 | 1,710 | 5,000 | 140 | 7 |
| 3940005 | 8717365020209 | 1.5 | 2.23-4 | PKA-G-4 | 2,290 | 4,000 | 146 | 7 |
| 3940006 | 8717365020308 | 1.5 | 2.23-4 | PKA-G-5 | 2,290 | 5,000 | 156 | 3 |