



Manually operated mobile lifting table

Product information



The ergonomic solution for bringing parts and tools to work height when working on machines.

Type HT: hand-operated lifting table.

Type D: double scissors for even more lift height.

Properties

- Hydraulic system provides for a higher level of safety.
- Foot pedal for lifting.
- Controllable descent rate by means of control lever.
- REMA movable lifting tables are fitted with two fixed wheels and two steer wheels with brake.
- HT-15 is equipped with foldable push handle, other types have fixed push handle.

Marking: According to standard, CE-marked

Standard: EN 1570, EN 12100

| Part code | GTIN No. | WLL ton | Model | Wheels diameter mm | Platform size mm | Min height mm | Max. lifting height mm | Weight kg | Delivery time |
|-----------|---------------|---------|--------|--------------------|------------------|---------------|------------------------|-----------|---------------|
| 3460015 | 8717365000355 | 0.15 | HT-15 | 100 | 700 x 450 | 260 | 765 | 41 | 3 |
| 3460025 | 8717365000362 | 0.25 | HT-25 | 125 | 815 x 500 | 310 | 910 | 78 | 3 |
| 3460050 | 8717365000379 | 0.5 | HT-50 | 150 | 1010 x 520 | 420 | 1,010 | 118 | 3 |
| 3460150 | 8717365016349 | 0.5 | HT-50D | 150 | 1010 x 520 | 435 | 1,585 | 168 | 3 |
| 3460075 | 8717365000386 | 0.75 | HT-75 | 150 | 1010 x 520 | 420 | 1,010 | 120 | 3 |
| 3460100 | 8717365000393 | 1 | HT-100 | 150 | 1010 x 520 | 430 | 955 | 145 | 7 |