


DLB brake winch

Product information



Properties

- Zinc-plated housing (DL2500G has a ungalvanized drum).
- Fitted with automatic load pressure brakes.
- For extra safety, they are fitted with locking pawls.

Standard delivery

- Does not include cable.

Options

- Steel wire rope according DIN 3060 with safety hook.
- Sling belt according DIN 3060 with safety hook.

[... Read more](#)


Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

Warning: For lifting, select another wire rope diameter, taking tensile strength into consideration. Minimum load required for winch to operate properly.

DLB brake winch

Blueprint



Technical data

| Part code | GTIN No. | WLL ton | Model | Rope Ø mm | Lift/crank turn (mm) | Gear ratio | Max. reel capacity mm | Drum mm | Length handle mm | Hand force max. kg | Weight kg |
|-----------|---------------|---------|------------|-----------|----------------------|------------|-----------------------|---------|------------------|--------------------|-----------|
| 2117010 | 8717365110580 | 0.159 | DLB-350A | 3 | 22.5 | 3.2 :1 | 25 | 26 x 52 | 178 | 10 | 3 |
| 2117011 | 8717365008979 | 0.36 | DLB-800AG | 4 | 36 | 4.4 :1 | 23 | 48 x 53 | 178 | 12 | 3 |
| 2117013 | 8717365008986 | 0.545 | DLB-1200AG | 5 | 39 | 5.4 :1 | 19.7 | 64 x 51 | 238 | 19 | 4 |
| 2117015 | 8717365008993 | 0.68 | DLB-1500AG | 6 | 40 | 5.4:1 | 15.1 | 64 x 62 | 305 | 18 | 5 |
| 2117016 | 8717365009006 | 0.905 | DLB-2000AG | 7 | 30 | 17.3 :1 | 8.9 | 64 x 54 | 238 | 8 | 7 |
| 2117017 | 8717365009013 | 1.135 | DLB-2500G | 8 | 23 | 12.0 :1 | 7.4 | 79 x 66 | 244 | 13 | 12 |