

RWL worm gear winch with freewheel system

Product information



Properties

- Braked design.
- Crank gradually adjustable in length.
- Drum and shafts provided with bearings.
- Freewheel, through protected pawl system.
- Powdercoating RAL2004.

Standard delivery

- Does not include wire rope.

Option

- Steel wire rope on request and hook with safety latch.


... [Read more](#)

Marking: According to standard, CE-marked

Standard: EN 12100, EN 13157

RWL worm gear winch with freewheel system

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Model	Rope Ø mm	WLL top layer ton	Gear ratio	Max. reel capacity mm	Length handle mm	Weight kg
2018001	8717365259296	0.25	RWL-250	5	0.075	15:1	20	250/100	11
2018003	8717365259302	0.5	RWL-500	6	0.3	24:1	30	250/100	17
2018005	8717365259319	1	RWL-1000	10	0.55	26:1	35	350/100	36

Model	A	B	C	D	F	G	H	J	K	L	M	N	Q	
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
RWL-250	167	332	150	202	137	100	26	13	118	11	89	80	99	24.5
RWL-500	195	367												