

WW worm gear winches

Product information



REMA[®]

Properties

- Load pressure brake.
- Adjustable crank length; backwind-free.
- Drums and axes run on needle bearings.
- Models above load capacity of 2 kg have two speeds, which is operated by changing the crank over.
- Paint finish and enamel varnish are standard.

Standard delivery

- Does not include wire rope.

Option

- Steel wire rope on request.


[... Read more](#)

Marking: According to standard, CE-marked

Standard: EN 13157, EN 12100

WW worm gear winches

Blueprint



Technical data

Part code	GTIN No.	WLL ton	Model	Rope Ø mm	WLL top layer ton	Lift/crank turn (mm)	Max. reel capacity mm	Hand force max. kg	Weight kg
2016001	8717365008771	0.25	WW-250	4	0.095	17	104	3.5	13
2016003	8717365008788	0.5	WW-500	6	0.239	20	78	9	16
2016005	8717365008795	1	WW-1000	8	0.542	13	63	15.5	26
2016007	8717365008801	1.5	WW-1500	10	0.845	9	41	19	28
2016009	8717365008818	2	WW-2000	12	1.129	12/6	46	22/13	60
2016011	8717365008825	3	WW-3000	14	1.861	11/6	52	27/14	78
2016012	8717365024269	4	WW-4000	16	2.39	11/4	52	35/13	80
2016013	8717365008849	5	WW-5000	18	3.165	12/4	40	58/17	115

Type	A	B	C	D	G	H	J	K	L	M	N	O	P	R	S
WW-250	238	145	100	192	106	102	48	14	160	191	15	410	280	171	130
WW-500	269	160	115	223	107	131	70	14	190	221	15	440	325		