



RSL - Electric Scaffold Winch 230 V

Product information

NEW

The Rema® RSL Scaffold Winch, a powerful single-phase lifting solution capable of handling loads up to 300 kg with a working height of 30 meters, perfect for safe and efficient lifting on any construction site.

Features

- Safety hook for secure load handling.
- 30 meters working height for extensive reach.
- Operates on 230V single-phase for easy integration.
- Emergency stop for enhanced safety in operation.

Marking: CE-marked

| Part code | Diameter mm | WLL ton | Lifting height m | Lifting speed m/min | Number of falls | Model | Weight kg | Delivery time |
|-----------|----------------|------------|---------------------|------------------------|-----------------|-----------------------|--------------|---------------|
| 2386001 | 4 | 0.15 | 30 | 15 | 1 | RSL-150 | 20 | 7 |
| 2386011 | - | 0.15 | - | - | - | Support arm RSL-150 | - | 7 |
| 2386003 | 5 | 0.2 | 30 | 20.1 | 1 | RSL-200 | 26 | 7 |
| 2386013 | - | 0.2 | - | - | - | Support arm RSL-200 | - | 7 |
| 2386017 | - | 0.2 | - | - | - | Clamp set RSL-150/200 | - | 7 |
| 2386005 | 5 | 0.3 | 30 | 20.1 | 1 | RSL-300 | 43 | 7 |
| 2386015 | - | 0.3 | - | - | - | Support arm RSL-300 | - | 7 |
| 2386019 | - | 0.3 | - | - | - | Bracket RSL-300 | - | 7 |
| 2386007 | - | - | - | - | - | Stand 195-300 cm | - | 7 |
| 2386009 | - | - | - | - | - | Stand 101-145 cm | - | 7 |

Blueprint

