



## Stainless steel sling 1-leg RCM-RCL-RCB

### Product information



Rema®'s Grade 6 Stainless Steel Chain Slings are meticulously crafted using top-tier stainless steel (AISI 316), our slings are not just durable but also versatile. With the availability of individual components, we ensure a sustainable and customizable solution tailored to your specific lifting requirements. Our stainless steel assemblies are trusted across a myriad of industries such as construction, food & beverage, healthcare, aerospace, marine, and beyond.

#### Utilization Features:

1. **Durability:** Made with premium AISI 316 stainless steel, ensuring longevity and resistance to corrosion.
2. **Versatility:** Suitable for a range of lifting operations with various assembly options.
3. **Safety:** Comes with a CE-mark and a safety factor of 4, ensuring utmost safety during operations.
4. **Adaptability:** Individual component availability for a tailored lifting solution.

#### Markets/Applications:

- **Construction:** Ideal for heavy-duty lifting and construction site operations.
- **Food & Beverage:** Stainless steel ensures hygiene and cleanliness, making it perfect for food-related lifting tasks.
- **Medical:** Suitable for lifting medical equipment and supplies.
- **Aerospace:** Can be used for lifting aerospace components.
- **Marine:** Resistant to corrosion, making it perfect for marine applications.

RC stainless steel chain | masterlink RCM | connecting link RCL | clevis sling hook RCB | AISI 316 TAG

**Marking:** CE-marked

**Safety factor:** 4

**Grade:** 6

Part code	GTIN No.	Chain diameter mm	WLL ton	EWL m	Model	Weight kg	Delivery time
2689106-1	8717365185656	6	0.9	1	900KG-6MM-RCM-RCB-1M	1.57	7
2689106-1.5	8717365184963	6	0.9	1.5	900KG-6MM-RCM-RCB-1,5M	1.86	7
2689106-2	8717365184970	6	0.9	2	900KG-6MM-RCM-RCB-2M	2.15	7
2689107-1	8717365184987	7	1.25	1	1250KG-7MM-RCM-RCB-1M	2.59	7
2689107-1.5	8717365184994	7	1.25	1.5	1250KG-7MM-RCM-RCB-1.5M	3.15	7
2689107-2	8717365185007	7	1.25	2	1250KG-7MM-RCM-RCB-2M	3.7	7
2689108-1	8717365185014	8	1.6	1	1600KG-8MM-RCM-RCB-1M	3.2	7
2689108-1.5	8717365185021	8	1.6	1.5	1600KG-8MM-RCM-RCB-1.5M	4.04	7
2689108-2	8717365185038	8	1.6	2	1600KG-8MM-RCM-RCB-2M	4.88	7
2689110-1	8717365185045	10	2.5	1	2500KG-10MM-RCM-RCB-1M	6.37	7
2689110-1.5	8717365185052	10	2.5	1.5	2500KG-10MM-RCM-RCB-1.5M	8.26	7
2689110-2	8717365185069	10	2.5	2	2500KG-10MM-RCM-RCB-1M	10.14	7
2689113-1.5	8717365185083	13	4.25	1.5	4250KG-13MM-RCM-RCA-1.5M	5.63	7
2689113-1	8717365185076	13	4.25	1	4250KG-13MM-RCM-RCA-1M	10.74	7
2689113-2	8717365185090	13	4.25	2	4250KG-13MM-RCM-RCA-2M	16.36	7