

Stainless steel sling 2-leg RCM-RCL-RCB

Product information



Rema®'s Grade 6 Stainless Steel Chain Slings are meticulously crafted using top-tier stainless steel (AISI 316), our slings are not just durable but also versatile. With the availability of individual components, we ensure a sustainable and customizable solution tailored to your specific lifting requirements. Our stainless steel assemblies are trusted across a myriad of industries such as construction, food & beverage, healthcare, aerospace, marine, and beyond.

Utilization Features:

1. **Durability:** Made with premium AISI 316 stainless steel, ensuring longevity and resistance to corrosion.
2. **Versatility:** Suitable for a range of lifting operations with various assembly options.
3. **Safety:** Comes with a CE-mark and a safety factor of 4, ensuring utmost safety during operations.
4. **Adaptability:** Individual component availability for a tailored lifting solution.

Markets/Applications:

- **Construction:** Ideal for heavy-duty lifting and construction site operations.
- **Food & Beverage:** Stainless steel ensures hygiene and cleanliness, making it perfect for food-related lifting tasks.
- **Medical:** Suitable for lifting medical equipment and supplies.
- **Aerospace:** Can be used for lifting aerospace components.
- **Marine:** Resistant to corrosion, making it perfect for marine applications.

Link to components

- 2 x RC stainless steel chain | masterlink RCM | 2 x connecting link RCB | [Read more](#)

Marking: CE-marked

Safety factor: 4

Grade: 6

Stainless steel sling 2-leg RCM-RCL-RCB

Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	WLL Straight Lift ton	WLL 0-45° t	WLL 45-60° t	Length	Model	Weight kg
2689206-1	8717365185106	6	1.26	1.26	1.26	0,900	1	1.26T-6MM-RCM-RCB-1M	2.6
2689206-1,5	8717365185113	6	1.26	1.26	1.26	0,900	1.5	1.26T-6MM-RCM-RCB-1.5M	3.18
2689206-2	8717365185120	6	1.26	1.26	1.26	0,900	2	1.26T-6MM-RCM-RCB-2M	3.76
2689207-1	8717365185137	7	1.75	1.75	1.75	1,250	1	1.75T-7MM-RCM-RCB-1M	4.64
2689207-1,5	8717365185144	7	1.75	1.75	1.75	1,250	1.5	1.75T-7MM-RCM-RCB-1.5M	5.75
2689207-2	8717365185151	7	1.75	1.75	1.75	1,250	2	1.75T-7MM-RCM-RCB-2M	6.86
2689208-1	8717365185168	8	2.24	2.24	2.24	1,600	1	2.24T-8MM-RCM-RCB-1M	6.05
2689208-1,5	8717365185175	8	2.24	2.24	2.24	1,600	1.5	2.24T-8MM-RCM-RCB-1.5M	7.73
2689208-2	8717365185182	8	2.24	2.24	2.24	1,600	2	2.24T-8MM-RCM-RCB-2M	9.41
2689210-1	8717365185199	10	3.5	3.5	3.5	2,500	1	3.5T-10MM-RCM-RCB-1M	12.28
2689210-1,5	8717365185205	10	3.5	3.5	3.5	2,500	1.5	3.5T-10MM-RCM-RCB-1.5M	16.05
2689210-2	8717365185212	10	3.5	3.5	3.5	2,500	2	3.5T-10MM-RCM-RCB-1M	19.82
2689213-1	8717365185229	13	5.95	5.95	5.95	4,250	1	5.95T-13MM-RCM-RCA-1M	21.18
2689213-1,5	8717365185236	13	5.95	5.95	5.95	4,250	1.5	5.95T-13MM-RCM-RCA-1.5M	26.8
2689213-2	8717365185243	13	5.95	5.95	5.95	4,250	2	5.95T-13MM-RCM-RCA-2M	32.42