



REMA AluFlex 360 hand chain hoist

Product information

The REMA® lightweight aluminium hand chain hoist offers maximum flexibility and safety. Thanks to its 360° rotatable design, you can lift and position loads from virtually any angle, even in confined spaces. Its low weight reduces physical strain on the user, which directly contributes to better ergonomics. Together with its well-thought-out, safe design, you can work quickly, accurately and comfortably.

Features

- Lightweight: Aluminium housing
- 360° rotatable: Full rotation hand chain
- Ergonomic: Operation from almost any angle
- Load pressure brake: Holds loads at any desired height
- Double pawl system
- Compact: Compact design with low installation height
- High-quality European load chain: Complies with EN818-7
- Available in capacities 250 and 500 kg

Standard delivery

- 3 m lifting height. (max. distance between upper and lower hooks).
- 2,5 m operating height.

Option

- Available in any other hoisting and operational heights.

Marking: CE-marked, UKCA-marked

Part code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Construction height mm	Hand force max. kg	A mm	B mm	C mm	Hmin mm	Weight kg	Delivery time
0030001-3	8717365071805	0.25	3	1	AF360/250KG/3M	3,2 x 9,0	2,5 x 14,0	240	14.98	89.5	84	25	240	2.8	7
0030001-4	8717365076428	0.25	4	1	AF360/250KG/4M	3,2 x 9,0	2,5 x 14,0	240	14.98	89.5	84	25	240	3.2	7
0030001-5	8717365076435	0.25	5	1	AF360/250KG/5M	3,2 x 9,0	2,5 x 14,0	240	14.98	89.5	84	25	240	3.6	7
0030001-6	8717365076442	0.25	6	1	AF360/250KG/6M	3,2 x 9,0	2,5 x 14,0	240	14.98	89.5	84	25	240	4	7
0030001-7	8717365076459	0.25	7	1	AF360/250KG/7M	3,2 x 9,0	2,5 x 14,0	240	14.98	89.5	84	25	240	4.4	7
0030001-8	8717365076466	0.25	8	1	AF360/250KG/8M	3,2 x 9,0	2,5 x 14,0	240	14.98	89.5	84	25	240	4.8	7
0030001-9	8717365076473	0.25	9	1	AF360/250KG/9M	3,2 x 9,0	2,5 x 14,0	240	14.98	89.5	84	25	240	5.2	7
0030001-10	8717365076411	0.25	10	1	AF360/250KG/10M	3,2 x 9,0	2,5 x 14,0	240	14.98	89.5	84	25	240	5.6	7
0030003-3	8717365076503	0.5	3	1	AF360/500KG/3M	4,3 x 12,0	3,5 x 20,0	270	18.7	103	102	30	270	4.8	7
0030003-4	8717365076510	0.5	4	1	AF360/500KG/4M	4,3 x 12,0	3,5 x 20,0	270	18.7	103	102	30	270	5.6	7
0030003-5	8717365076527	0.5	5	1	AF360/500KG/5M	4,3 x 12,0	3,5 x 20,0	270	18.7	103	102	30	270	6.4	7
0030003-6	8717365076534	0.5	6	1	AF360/500KG/6M	4,3 x 12,0	3,5 x 20,0	270	18.7	103	102	30	270	7.2	7
0030003-7	8717365076541	0.5	7	1	AF360/500KG/7M	4,3 x 12,0	3,5 x 20,0	270	18.7	103	102	30	270	7.9	7
0030003-8	8717365076558	0.5	8	1	AF360/500KG/8M	4,3 x 12,0	3,5 x 20,0	270	18.7	103	102	30	270	8.7	7
0030003-9	8717365076565	0.5	9	1	AF360/500KG/9M	4,3 x 12,0	3,5 x 20,0	270	18.7	103	102	30	270	9.5	7
0030003-10	8717365076497	0.5	10	1	AF360/500KG/10M	4,3 x 12,0	3,5 x 20,0	270	18.7	103	102	30	270	10.3	7

Blueprint

