

Fall Arrest Block HWPS/E

Product information



Robust, retractable fall arrest device delivered with galvanized- (HWPS) or stainless-steel wire and swivel (HWPSE).

The device has an internal energy-absorber and hook with fall indicator, and the plastic housing makes its weight and maintenance low.

Approved for vertical and horizontal use.

Edge tested: Tested at sharp edges, $R \geq 0,5 \text{ mm}$ (CNB/P/11.060 2008 sharp edge Type A)

Carabiner: IKV21 (Lk = 186mm) small swivel snap hook (opening $\varnothing 26 \text{ mm}$)
Can be delivered with other carabiners or scaffolding hooks up on request.

The blocks can be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

[... Read more](#)

Material: Body: Plastic


Marking: According to standard, CE-marked

Temperature range: -40°C to $+50^{\circ}\text{C}$.

Standard: EN 360

Fall Arrest Block HWPS/E

Blueprint



Technical data

Part code	Code	Max. number of persons	Length m	Description	Max load kg	L mm	B mm	T mm	Weight kg
1790121	HWPS 3	1	3	Galvanized wire	136	390	104	78	1.9
1790125	HWPS 6	1	6	Galvanized wire	136	420	145	80	2.5
1790127	HWPS 9	1	9	Galvanized wire	136	460	168	88	3.2
1790129	HWPS 12	1	12	Galvanized wire	136	500	195	95	4.9
1790131	HWPS 18	1	18	Galvanized wire	136	540	220	97	6.3