

Chariot à vis REMA RMBT

Informations du produit



REMA[®]

Properties

- Suitable for flat or bevel profiles.
- Equipped with solid steel wheels with maintenance-free bearings.
- Compact and lightweight.
- Quick assembly through threaded adjustable.
- Safe by locking lever.
- With wheel rupture supports.

... [En savoir plus](#)


Marquage: Selon la norme, Marqué CE

Norme: EN 12100, EN 13157

Note: Seulement 7,5 kg RMBT-2T

Chariot à vis REMA RMBT

Dessin technique



Données techniques

| Réf. | GTIN No. | CMU (kg) | Largeur de fer | Modèle | A mm | B mm | C mm | D mm | E mm | G mm | H mm | J mm | K mm | Poids (kg) |
|---------|---------------|----------|----------------|----------|------|------|------|------|-------|------|------|------|------|------------|
| 0940002 | 8717365114786 | 2 000 | 76-203 | RMBT-2T | 272 | 176 | 360 | 54,5 | 72 | 16 | 8 | 21 | 95 | 7 |
| 0940003 | 8717365114793 | 3 000 | 76-203 | RMBT-3T | 381 | 270 | 475 | 82,5 | 118,5 | 25,5 | 14 | 33 | 113 | 25 |
| 0940006 | 8717365114809 | 6 000 | 105-305 | RMBT-6T | 429 | 356 | 560 | 125 | 116 | 26 | 16 | 34 | 100 | 52 |
| 0940010 | 8717365114816 | 10 000 | 160-305 | RMBT-10T | 541 | 430 | 630 | 145 | 119 | 32 | 16 | 41 | 110 | 74 |