REMA® Work made easy.
HOISTING & LIFTING



YA lever hoist

Product information

REMA®

Model Rema® YA lever hoist is a robust lever hoist suitable for lifting, pulling, spanning and clamping in any directions.

Properties

- Grade 10 Galvanized load chain with high tensile strength (EN 818/7).
- Compact construction and very low self-weight.
- Reliable self-locked brake which will retain the load at every required height.
- Hooks provided with safety latches.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Patented guide for the load chain.
- A double spring on each catch for additional safety.

Standard delivery

- 1,5 m lifting height (max distance between top and bottom hookpositions).

Option

- Available in other lifting heights.

Marking: According to standard, CE-marked
Standard: EN 818-7, EN 13157

Part Code	GTIN No.	WLL ton	Lifting height m	Model	Load Chain dia x pitch mm	Max. hand force on crank kg	Chain falls	Construction height mm	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
0208003-1,5M	8717365258794	1	1,5	YA/1000KG/1,5M	5.6 x 17.1	37	1	312	144	91	122	268	28	43	312	6,2
0208003-3M	8717365163715	1	3	YA/1000KG/3M	5.6 x 17.1	37	1	312	144	91	122	268	28	43	312	7,3
0208003-4.5	8717365264672	1	4,5	YA/1000KG/4,5M	5.6 x 17.1	37	1	312	144	91	122	268	28	43	312	8,4
0208003-6	8717365264689	1	6	YA/1000KG/6M	5.6 x 17.1	37	1	312	144	91	122	268	28	43	312	9,5
0208005-1,5M	8717365258817	1,6	1,5	YA/1600KG/1,5M	7.1 x 21	30	1	352	162	99	136	310	29	43	352	9,5
0208005-3M	8717365163722	1,6	3	YA/1600KG/3M	7.1 x 21	30	1	352	162	99	136	310	29	43	352	11,3
0208005-4.5	8717365264702	1,6	4,5	YA/1600KG/4,5M	7.1 x 21	30	1	352	162	99	136	310	29	43	352	13,1
0208005-6	8717365264719	1,6	6	YA/1600KG/6M	7.1 x 21	30	1	352	162	99	136	310	29	43	352	14,9
0208007-1,5M	8717365260032	3,2	1,5	YA/3200KG/1,5M	9.0 x 27.2	37	1	420	186,5	104	180	310	36	53	420	15,5
0208007-3M	8717365163739	3,2	3	YA/3200KG/3M	9.0 x 27.2	37	1	420	186,5	104	180	310	36	53	420	18,2
0208007-4.5	8717365264733	3,2	4,5	YA/3200KG/4,5M	9.0 x 27.2	37	1	420	186,5	104	180	310	36	53	420	20,9
0208007-6	8717365264740	3,2	6	YA/3200KG/6M	9.0 x 27.2	37	1	420	186,5	104	180	310	36	53	420	23,6
0208009-1,5M	8717365260056	6,3	1,5	YA/6300KG/1,5M	9.0 x 27.2	38	2	564	186,5	104	235	310	47	70	564	26,5
0208009-3	8717365264757	6,3	3	YA/6300KG/3M	9.0 x 27.2	38	2	564	186,5	104	235	310	47	70	564	32
0208009-4.5	8717365264764	6,3	4,5	YA/6300KG/4,5M	9.0 x 27.2	38	2	564	186,5	104	235	310	47	70	564	37,5
0208009-6	8717365264771	6,3	6	YA/6300KG/6M	9.0 x 27.2	38	2	564	186,5	104	235	310	47	70	564	43
0208011-1,5M	8717365260070	9	1,5	YA/9000KG/1,5M	9.0 x 27.2	39	3	589	186,5	104	300	310	73	85	689	42
0208011-3	8717365264788	9	3	YA/9000KG/3M	9.0 x 27.2	39	3	589	186,5	104	300	310	73	85	689	50,1
0208011-4.5	8717365264795	9	4,5	YA/9000KG/4,5M	9.0 x 27.2	39	3	589	186,5	104	300	310	73	85	689	58,2
0208011-6	8717365264801	9	6	YA/9000KG/6M	9.0 x 27.2	39	3	589	186,5	104	300	310	73	85	689	66,3

Blueprint

