



KBT200OD low headroom hoist-trolley

Product information



Hand-operated trolley in combination with the Rema® Select 200OD hand chain hoist.
Only available in combination with the Rema® Select 200 OD manual chain hoist.

Properties

- Extremely low building height (135-235 mm).
- Suitable for beams with both straight and sloping flange.
- Maintenance-free ball bearings.
- Wheel rupture supports for extra safety.
- Hand chain operated trolley.
- Technical specifications for manual hoist see Rema® Select 200 OD chain hoist.

Standard delivery

- 3 meters lifting height (max. between top and bottom hook).
- 2.5 meters operation.

Option

- Available in other lifting and operating heights.

Marking: CE-marked

Part code	WLL ton	Number of falls	Model	Flange width mm	Load chain mm	Hand chain mm	Minimum radius mm	A mm	B1 mm	B2 mm	C1 mm	C2 mm	D1 mm	D2 mm	E1 mm	E2 mm	F mm	H mm	L mm	M1 mm	M2 mm	Weight kg	Delivery time
0923001	1	2	KBT200OD-1	74-150	5.0 X 15	5.0 X 23.7	2 500	554	206	234	129	151	117	223	217	134	27,5	135	348	40	18	69	3
0923003	2	2	KBT200OD-2	82-156	6.3 X 19.1	5.0 X 23.7	4 000	684	254	406	149	211	165	265	240	152	36,5	160	392	50	24	118	7
0923005	3,2	2	KBT200OD-3.2	103-223	8.0 X 24.2	5.0 X 23.7	4 500	765	279	461	169	236	165	325	240	173	44	190	499	55	28	181	3
0923007	5	4	KBT200OD-5	119-215	8.0 X 24.2	5.0 X 23.7	6 000	873	336	524	201	279	184	327	259	180	39	235	512	65	37	293	3
0923009	6,3	4	KBT200OD-6.3	119-215	8.0 X 24.2	5.0 X 23.7	6 000	873	336	524	201	279	184	327	259	180	39	235	512	65	37	296	3

Blueprint

