



YAM lever hoist

Product information



The Rema® YAM mini lever hoist is compact and a very low own weight. The required manual effort on the short handle (180 mm) remains low because the YAM is equipped with a gear transmission. The ideal tool for assembly work such as hoisting, pulling and tensioning.

Properties:

- Very low self weight (2,8 kg), compact.
- Hooks equipped with safety latches.
- Self locked brake holds the load at any desired height.
- Freewheel is possible in unloaded condition, by 1 operation.
- Hoist fitted with rubber anti-slip handle.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain Grade 10.

Standard delivery:

- 1,5 m lifting height (max. distance between top & bottom hooks).

Option:

- Available in other lifting heights.

Marking: According to standard, CE-marked

Standard: EN 818-7, EN 13157

Part Code	WLL kg	Lifting height m	Model	Load Chain dia x pitch mm	Max. hand force on crank kg	Chain falls	Construction height mm	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
0208002-1.5	500	1,5	YAM-500KG-1,5	4.3 x 12	35	1	240	113	69	92	180	24	36	240	2,8
0208002-3	500	3	YAM-500KG-3	4.3 x 12	35	1	240	113	69	92	180	24	36	240	3,4
0208002-4.5	500	4,5	YAM-500KG-4,5	4.3 x 12	35	1	240	113	69	92	180	24	36	240	4
0208002-6	500	6	YAM-500KG-6	4.3 x 12	35	1	240	113	69	92	180	24	36	240	4,6

