



Alpha ALHVDH 230V electric chain hoist

Product information



The ALHVDH 230 V electric chain hoist is a compact chain hoist.

The ALHVDH has a very low own weight (aluminum house). Can be used in many applications due to the high duty cycle in combination with a high lifting speed.

Properties

- Operation at the lower hook.
- Variable speed adjustable by turning the handle.
- Spiral control cable around the load chain.
- Slip clutch against overload.
- Self locking brake that holds the load at any desired height.
- In case of overload, the hooks will gradually bend and do not suddenly break off.
- Galvanized load chain, class DAT (Grade 8).

Technical specification:

- Insulation class B.
- FEM 9.511 motor: 1Am.
- Power supply 230VAC.
- Protection class IP54.

Standard delivery

- 2,5 m lifting height (max distance between top and lower hook).
- 4 m power cable.
- Plastic chain container for 3 m lifting height.
- Trolley not included.

Option

• Push trolley.

Marking: CE-marked

Part Code	GTIN No.	WLL ton	Lifting height m	Number of falls	Model	Motor kW	Load Chain dia x pitch mm	Chain falls	Lifting speed m/min.	Duty rating % ED	Construction height mm	Weight kg
0513205	8717365109348	0,25	2,5	1	ALHVDH/250	0,6	4.0 x 12	1	0.9~10	25	673	22

Blueprint

